



TECHNICAL DATA SHEET

ATHENIT-KALKGLÄTTE

1. PRODUCT DESCRIPTION

2. PRODUCT PROPERTIES

- non-yellowing
- low stress
- environmentally friendly
- extremely vapour permeable
- fire behaviour: non-flammable
- no synthetic binders
- no plant-based resins
- odourless

MATERIAL CHARACTERISTICS:

- Maximum grain size: 0.1 mm
- Maximum layer thickness: 1 mm

CLASSIFICATION:

- Diffusion-equivalent air layer thickness (sd-value): $\leq 0,02$ m

COLOUR SHADES:

Natural white, tinting on request
Tintable up to 3 % with KEIM decor paint powder.

3. APPLICATION INSTRUCTIONS

CLEANING OF TOOLS:

Clean immediately with water.

4. PACKAGING

Container content	Unit of measure	Quantity on pallet	Type of container
24	kg	24	bucket

5. STORAGE

max. storage time	Storage conditions
12 months	keep container tightly sealed. frost-free

TECHNICAL DATA SHEET – ATHENIT-KALKGLÄTTE

6. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code:

7. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet.

GISCODE:

8. GENERAL INFORMATION

Mixing with products not part of the system or other foreign additives is not permitted.

9. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

