



TECHNICAL DATA SHEET

KEIM SOLIPRIM

1. PRODUCT DESCRIPTION

KEIM Soliprim is a silicate special primer for interior use based on a binder combination of silica sol and hydrosol.

2. FIELD OF APPLICATION

KEIM Soliprim is used

- for levelling different absorbencies of mineral and organic substrates, load-bearing old coatings or mixed substrates.
- for fixing and consolidating chalking or sanding substrates.
- for optimising the surface homogeneity of subsequent coats, especially in difficult lighting conditions.

3. PRODUCT PROPERTIES

- silicifies insolubly with the substrate
- good penetration property
- adhesion-promoting
- highly substrate-solidifying
- equalising
- permeable
- microporous
- no solvents added
- low-odour

MATERIAL CHARACTERISTICS:

- Density: approx. 1.0 - 1.1 g/cm³
- Organic content: < 5 %
- pH value: approx. 9

CLASSIFICATION:

- Diffusion-equivalent air layer thickness (sd-value): < 0,01 m

COLOUR SHADES:

milky

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

The substrate must be dry, sound and free from grease.

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be ≥ 5 °C.

APPLICATION:

KEIM Soliprim apply preferably undiluted by brush. Roller or spray application is also possible. Avoid glossy areas. In case of highly absorbent substrates, two wet-on-wet applications may be necessary.

Note: KEIM Soliprim cannot be used as a thinner.

TECHNICAL DATA SHEET – KEIM SOLIPRIM

CONSUMPTION:

approx. 0,15 l/m² for a single coating.

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

CLEANING OF TOOLS:

Clean immediately with water.

5. PACKAGING

Container content	Unit of measure	Quantity on pallet	Type of container
20	l	24	jerry can
5	l	96	jerry can

6. STORAGE

max. storage time	Storage conditions
12 months	keep container tightly sealed. cool frost-free protected from heat and direct sun.

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

EC WASTE CODE:

Waste code: 08 01 11 *

8. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet.

GISCODE:

GIS code: BSW 50

9. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

10. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de