



KEIM MARANO[®]-FILLER

EVERY MINUTE COUNTS!

KEIM Marano®-Pro

UNIVERSAL HAND APPLICATION FILLER

- Fast drying
- Very high degree of whiteness
- Fine surface texture
- Full and partial surface application

KEIM Marano®-Roll

LIGHT FILLER FOR ROLLER APPLICATION

- Very filling
- Light formulation
- Up to 30% time saving when roller-applied than compared to a trowel application by hand

KEIM Marano®-Light

ULTRALIGHT FILLER FOR AIRLESS APPLICATION

- Effort-saving application thanks to ultralight formulation
- Efficient working due to excellent properties for airless application
- Reduced sanding dust

COMPARISON: FLYING DUST FROM SANDING ACCUMULATED ON THE FLOOR.

Common manual filler

Fine sanding dust is spread throughout the room.

KEIM Marano-Light

Sanding dust forms coarse accumulations that fall faster to the floor.



Product	Consumption per m ² und mm	Light formula	Max. layer thickness	Org. content	Degree of whiteness	Surface fineness	Sandability with sandpaper 120 grit	Filling properties	Recommended airless nozzle	Drying time at 23 °C / 50% air humidity**
KEIM Marano-Pro	1.75 kg	-	4 mm	<5%	++++	+++	++	++	545	approx. 9-12 h
KEIM Marano-Roll	approx. 1.1 l	+++	5 mm	<5%	++	++	+++	++++	-	approx. 24 h
KEIM Marano-Light	approx. 1 l	++++	5 mm	<5%	+++	+++	++++	+++	525	approx. 24 h

** Depending on building moisture and layer thickness

KEIM FILLER FOR ALL PURPOSES



TIME SAVING

13%

A PERFECT RESULT REQUIRES A PERFECT BASE

The filler range from KEIM provides the optimal bases for subsequent coating. Gypsum plasterboard, render surfaces or concrete, in new construction or for renovation – with KEIM fillers you achieve top results.

Open the bucket and start right away! KEIM Marano filler products are ready-for-use which means that mixing of powder material and water at the construction site is unnecessary. Actually 8 minutes (13%) of valuable work time is saved when working one hour applying the filler.

KEIM Marano is optimised for every application case and provides highly efficient solutions for every construction site situation thanks to certain product concepts for paint roller and spray paint machine application.

CHARACTERISTICS

- Ready-for-use
- Uncomplicated and reliable application
- Easy to apply and to smooth down
- Smooth consistency
- Very good sanding
- Optimised for any application case





KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 (0)821 4802-0 / Fax +49 (0)821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 (0)35456 676-0 / Fax +49 (0)35456 676-38
www.keim.com/info@keimfarben.de

KEIM. COLOURS FOR EVER.