

Page 1/14

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 14.0 (replaces version 13.0) Printing date 10.05.2022 Revision: 10.05.2022

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: KEIM LOTEXAN-N
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture Hydrophobing agent/ water repellent
- · Uses advised against All other uses are not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf

Tel. +49 (0)821 4802-0

Fax +49 (0)821 4802-210

www.keim.com / info@keimfarben.de

· Further information obtainable from:

Product safety department Telefon: 49(0)821/4802-138 E-Mail: sdb.info@keimfarben.de

· 1.4 Emergency telephone number:

GBK GmbH Global Regulatory Compliance Emergency number: +49(0)6132/84463

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or

repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms









GHS02 GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrodesulfurized heavy (< 0,1% benzene)

(Contd. on page 2)



Page 2/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 1)

#### · Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P315 Get immediate medical advice/attention.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378 In case of fire: Use CO2, powder or water spray to extinguish.

P405 Store locked up.

P501 Dispose of contents/container in accordance with regional/national regulations.

#### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

### Information concerning particular hazards for human and environment:

Has a narcotizing effect.

Contact with skin and inhalation of aerosols / vapours of the preparation should be avoided.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicablevPvB: Not applicable

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:	Dangerous components:		
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy (< 0,1% benzene)	50-100%	
Index number: 649-330-00-2 Reg.nr.: 01-2119458049-33- XXXX	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066		
CAS: 34396-03-7 EINECS: 251-995-5	Trimethoxy(2,4,4-trimethylpentyl)silane  Flam. Liq. 3, H226	≤2.5%	
CAS: 3648-18-8 EINECS: 222-883-3 Reg.nr.: 01-2119979527-19- XXXX	dioctyltin dilaurate  Repr. 1B, H360D; STOT RE 1, H372	<0.15%	
	(0.	antd on nago 2)	

(Contd. on page 3)



Page 3/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

Trade name: KEIM LOTEXAN-N

CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35- XXXX		ontd. of page 2) ≥0.25-<1%
· SVHC		
	EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35- XXXX	CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35- XXXX  Solvent naphtha (petroleum), light arom. (< 0,1% Benzene) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information:

When seeing the doctor we suggest to present this safety data sheet.

Immediately remove any clothing soiled by the product.

In case of unconsciousness place patient stably in side position for transportation.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not use solvents or thinners.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse mouth and throat well with water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness

Dizziness

Nausea

Coughing

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

carbon oxide (COx)

silicon dioxid (SiO2)

Flammable gases/vapours

(Contd. on page 4)



Page 4/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 3)

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Specila protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

In case of fire do not breathe smoke, fumes and vapours.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Do not inhale fumes.

Avoid contact with skin and eyes.

Respect the protection rules (see section 7 a. 8).

Wear protective equipment. Keep unprotected people away.

#### 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Follow local governmental rules and regulations.

### 6.3 Methods and material for containment and cleaning up:

Absorb with non-combustible liquid-binding material (sand, earth, diatomite, vermiculite).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Clear contaminated areas thoroughly.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Do not inhale aerosols.

Keep receptacles tightly sealed.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

See item 8 (8.2) for information about suitable protective equipment and technical precautions. Respect the protection rules.

#### Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

(Contd. on page 5)



Page 5/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 4)

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Keep in the original containers in a cool and dry place.

Drip pan to be provided.

- Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Protect from frost.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
64742-82-1 Naph	64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy (< 0,1% benzene)		
AGW (Germany) Long-term value: 300 mg/m³ TRGS 900, Nr. 2.9, Kohlenwasserstoffgemische 64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1% Benzene)			
			AGW (Germany) Long-term value: 100 mg/m³ TRGS 900, Nr. 2.9, Kohlenwasserstoffgemische
· DNELs			

	11100 000, 1111 210, 11	ermenne en	
· DNELs			
64742-82-	64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy (< 0,1% benzene)		
Oral	Oral Long-term - systemic effects 21 mg/kg bw/day (consumer)		
Dermal	Long-term - systemic effects	21 mg/kg bw/day (worker)	
	Long-term - systemic effects	12 mg/kg bw/day (consumer)	
Inhalative	Long-term - systemic effects	330 mg/m³ (worker)	
	Long-term - systemic effects	71 mg/m³ (consumer)	
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1% Benzene)		
Oral	Long-term - systemic effects	11 mg/kg bw/day (consumer)	
Dermal	Long-term - systemic effects	25 mg/kg bw/day (worker)	
	Long-term - systemic effects	11 mg/kg bw/day (consumer)	
Inhalative	Long-term - systemic effects	150 mg/m³ (worker)	

· Additional information: The lists valid during the making were used as basis.

Long-term - systemic effects 32 mg/m³ (consumer)

(Contd. on page 6)



Page 6/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 5)

#### · 8.2 Exposure controls

#### · Individual protection measures, such as personal protective equipment

# General protective and hygienic measures:

Avoid contact with the eyes and skin.

Do not inhale aerosols.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Store protective clothing separately.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A/P2

#### · Hand protection

Only use chemical-protective gloves with CE-labelling of category III.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Protective gloves

## Material of gloves

suitable material e.g.:

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq$  0.4 mm

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Value for the permeation: level  $\geq$  6 (480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection Tightly sealed goggles

# · Body protection:

Solvent resistant protective clothing

After contact with skin wash thoroughly with water and apply lotion.

#### Environmental exposure controls

See Section 12 and 6.2

No further relevant information available.

DEN

(Contd. on page 7)



Page 7/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 6)

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:
Fluid
White
Aromatic
Not determined
Not determined

· Boiling point or initial boiling point and

boiling range >148 °C

· Lower and upper explosion limit

 $\begin{array}{lll} \cdot \ \, \text{Lower:} & 0.6 \ \text{Vol } \% \\ \cdot \ \, \text{Upper:} & 7 \ \text{Vol } \% \\ \cdot \ \, \text{Flash point:} & \sim 40 \ ^{\circ}\text{C} \\ \cdot \ \, \text{Ignition temperature:} & > 200 \ ^{\circ}\text{C} \\ \end{array}$ 

Decomposition temperature: Not determinedpH Not applicable

Viscosity:

Kinematic viscosityDynamic:Not determinedNot determined.

Solubility

· water: Insoluble

· Partition coefficient n-octanol/water (log

value) Not applicable • Vapour pressure at 20 °C: ~2.3 hPa

Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined
 Not applicable.

and may change with the time.

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, the formation

of explosive air/vapour mixtures is possible.

· Solvent content:

· **VOC (EC)** 93.20 %

· Change in condition

· Softening point/range

Oxidising properties: Not applicableEvaporation rate Not determined.

(Contd. on page 8)



Page 8/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

(Contd. of page 7)

classes
• Explosives Void
• Flammable gases

Information with regard to physical hazard

Flammable gases
Aerosols
Oxidising gases
Gases under pressure

Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

· Substances and mixtures, which emit

flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

Void

Void

# **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Stable under normal conditions of storage and use.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- · 10.4 Conditions to avoid

Heat

Flame

**Sparks** 

- · 10.5 Incompatible materials: oxidizing agents
- 10.6 Hazardous decomposition products:

In case of fire, the following can be released:

Carbon oxides (COx)

silicon dioxid (SiO2)

Flammable gases/vapours

No hazardous decomposition products if stored and handled as prescribed.

# **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)



Page 9/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

			(Contd. of page 8)
· LD/LC50	values rele	evant for classification:	
64742-82-	1 Naphtha	a (petroleum), hydrodesulfurized heavy (< 0,1% benzene)	
Oral	LD50	>15,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,400 mg/kg (rabbit) (OECD 402)	
Inhalative	Inhalative LC50/4 h 13.1 mg/l (rat) (OECD 403)		
64742-95-	6 Solvent	naphtha (petroleum), light arom. (< 0,1% Benzene)	
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>3,160 mg/kg (rabbit)	

#### · Skin corrosion/irritation

not primarily irritating on the skin

Has de-greasing effect on skin.

Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/irritation

In case of longer exposure, slightly irritating effect to the eyes is possible.

### during inhalation:

Vapours may cause drowsiness and dizziness.

Irritant effect possible.

# during swallowing:

May cause lung damage if swallowed.

Irritant effect possible

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure.

- · Aspiration hazard May be fatal if swallowed and enters airways.
- · Other information (about experimental toxicology):

Experimental analysis are not available.

The product was not tested. The statements on toxicology have been derived from the properties of the individual components.

- Subacute to chronic toxicity:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Not applicable
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

(Contd. on page 10)



Page 10/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

Trade name: KEIM LOTEXAN-N

	(Contd. of page 9)	
Naphtha (petroleum), hydrodesulfurized heavy (< 0,1% benzene)		
0.097 mg/l (daphnia) (21d)		
10 mg/l (daphnia) (OECD 202)		
4.6 mg/l (algae) (OECD 201)		
10 mg/l (fish) (OECD 203)		
0.13 mg/l (fish) (72h)		
64742-95-6 Solvent naphtha (petroleum), light arom. (< 0,1% Benzene)		
1-10 mg/l (algae)		
1-10 mg/l (fish)		
1-10 mg/l (invertebrates)		
	0.097 mg/l (daphnia) (21d) 10 mg/l (daphnia) (OECD 202) 4.6 mg/l (algae) (OECD 201) 10 mg/l (fish) (OECD 203) 0.13 mg/l (fish) (72h)  Solvent naphtha (petroleum), light arom. (< 0,1% Benzene) 1-10 mg/l (algae) 1-10 mg/l (fish)	

- · 12.2 Persistence and degradability Easily biodegradable
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable
- · vPvB: Not applicable
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects** No further relevant information available.
- · Additional ecological information:
- · AOX-indication:

According to our standard of knowledge the product does not contain any organic bounded halogen. The product has no influence on the waste water's AOX-value.

According to the formulation contains the following heavy metals and compounds from the EU guideline NO. 2006/11/EC:

According to our current data base the product does not consist of any heavy metals or substances of EU-directives 76/464/EWG.

· General notes:

Avoid transfer into the environment.

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

At present there are no ecotoxicological assessments.

The statements on ecotoxicology have been derived from the properties of the individual components.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

(Contd. on page 11)



Page 11/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

	(Contd. of page 10)	1
· European	n waste catalogue	
14 06 03*	other solvents and solvent mixtures	
15 02 02* absorbents, filter materials (including oil filters not otherwise specified), wiping clo		

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary with cleansing agents.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (Napht (petroleum), hydrodesulfurized heavy (< 0,1 benzene), Solvent naphtha (petroleum), light aro (< 0,1% Benzene)), MARINE POLLUTAN ENVIRONMENTALLY HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (Naphti (petroleum), hydrodesulfurized heavy (< 0,1 benzene), Solvent naphtha (petroleum), light aro (< 0,1% Benzene)), MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (Naphti (petroleum), hydrodesulfurized heavy (< 0,1 benzene), Solvent naphtha (petroleum), light aro (< 0,1% Benzene))
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
IATA	
3	
Class	3 Flammable liquids.
Label	3

(Contd. on page 12)



Page 12/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

**Trade name: KEIM LOTEXAN-N** 

	(Contd. of page 1
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous ubstances: Naphtha (petroleum) hydrodesulfurized heavy (< 0,1% benzene)
• Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-E A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml 3 D/E
	D/L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S (NAPHTHA (PETROLEUM) HYDRODESULFURIZED HEAVY (< 0,1° BENZENE), SOLVENT NAPHTH (PETROLEUM), LIGHT AROM. (< 0,1° BENZENE)), 3, III, MARINE POLLUTAN ENVIRONMENTALLY HAZARDOUS

DEN

(Contd. on page 13)



Page 13/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

Trade name: KEIM LOTEXAN-N

(Contd. of page 12)

# **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

For information on labelling please refer to section 2 of this document.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)

None of the ingredients is listed.

Regulation (EU) No 649/2012

3648-18-8 dioctyltin dilaurate

Annex I Part 1

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Other regulations, limitations and prohibitive regulations

The product is subject to Annex 2 of the Chemicals Prohibition Ordinance (ChemVerbotsV) - Requirements with regard to distribution

· Please note:

TRGS 200 (Germany)

TRGS 500 (Germany)

TRGS 510 (Germany)

TRGS 900 (Germany)

(Contd. on page 14)



Page 14/14

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.05.2022 Version number 14.0 (replaces version 13.0) Revision: 10.05.2022

Trade name: KEIM LOTEXAN-N

(Contd. of page 13)

#### · Substances of very high concern (SVHC) according to REACH, Article 57

3648-18-8 dioctyltin dilaurate

· Product-Code/Giscode: BSL50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360D May damage the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: KEIMFARBEN Germany, Product safety department
- · Version number of previous version: 13.0
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

VOC: Volatile Organic Compounds (USA, EÙ)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

AGW: Arbeitsplatzgrenzwert (Germany)

EC10: Effective concentration at 10% mortality rate.

EC50: Half maximal effective concentration.

LC10: Lethal concentration at 10% mortality rate.

NOEC: No observed effect concentration.

REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)

Flam. Liq. 3: Flammable liquids – Category 3

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.