



TECHNICAL DATA SHEET

KEIM STOSSVERBINDER

1. PRODUCT DESCRIPTION

H-connector made of aluminium without sealing shoe.

2. FIELD OF APPLICATION

For covering/connection of two window sill elements.

3. PRODUCT PROPERTIES

- easy to use
- fire behaviour: non-flammable (A1)
- resistant to aging

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Remove the protective film in the area where the accessory is placed on the window sill.

per window sill

APPLICATION:

Stoßverbinder is recommended for light-coloured surfaces from 3.0 m and for dark-coloured surfaces from 2.0 m. A second sealing layer is recommended to ensure that the windowsill withstands driving rain.

Connectors for outside and inside corners 90° or 135° on request.

5. PACKAGING

Product name	Projection	Pieces per unit	Type of container	Length
Stoßverbinder	50 - 500 mm	1	piece	

Further projections, moulded parts, surfaces, anodising and special colours on request.

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry

7. DISPOSAL

Waste code: 17 04 02

8. SAFETY INSTRUCTIONS

No particular indications.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

