



TECHNICAL DATA SHEET

KEIM APU-LEISTE MINI

1. PRODUCT DESCRIPTION

Connection profile as plastering and sealing strip with fabric, bendable protective flap for cover foil.

2. FIELD OF APPLICATION

For permanent connection joints indoors between frame or door frame and room air-conditioning systems. The movements from the building component and the room air-conditioning system are absorbed.

Suitable for window and door reveals.

Further instructions for use in the KEIM detailed plans.

3. PRODUCT PROPERTIES

- fire behaviour: hardly inflammable B1 according to 4102
- permeable
- resistant to aging

MATERIAL CHARACTERISTICS:

- Proven driving rain tightness, max. wind pressure: keine Angabe (Anwendung nur Innen)
- Fabric flag mesh width: 4 x 4 mm
- Fabric flag width: ca. 12,5 cm
- Colour shade: white

PERFORMANCE AND CRITERIAS OF SELECTION:

- Eignung: für helle Rahmen und hellen Putz für helle Rahmen und dunklen Putz oder umgekehrt
- Visible joints: Foam tape white

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Clean the frame. The frame must be dry, clean, even and free of adhesion-reducing layers. Before using adhesive profiles, an adhesive test is required. For this, clean a hidden area with a dry and clean tissue (without cleaning agents). Stick profile section (ca. 10 cm) and press firmly. After waiting for approx. 10 minutes, slowly remove the profile from the substrate. For an adhesive suitability the foam tape must stick to both surfaces (profile and substrate) = complete foam break. On critical substrates, e.g.: plastic windows, oiled or varnished wooden windows, powder or teflon coated metallic windows, the leakage of waxes, oils and plasticisers can never be fully excluded.

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be in the range between min. 5 °C and max. 30 °C.

CONSUMPTION:

approx. 1,1 m/m

APPLICATION:

Cut to size with anvil shears or suitable angle sander.

TECHNICAL DATA SHEET – KEIM APU-LEISTE MINI

KEIM APU-Leiste Mini is to be applied before the application of the base coat.

AFTERTREATMENT:

After the finish paint coat the protective flashing of KEIM APU-Leiste Mini is snapped off and removed.

5. DELIVERY FORM

Product name	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
Apu-Leiste Mini	2.40	25	60	carton

DELIVERY FORM ADDITIONAL INFORMATION

Delivery in cartons

6. STORAGE

Storage conditions
flat-lying in the outer cardboard avoid deflection dry frost-free

STORAGE INFORMATION

Observe the instruction leaflet in the packaging!

7. DISPOSAL

EC WASTE CODE:

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

9. GENERAL INFORMATION

CLASSIFICATION OF THE SEALING STRIP AFTER ITS MOVEMENT ABSORPTION

Elongation	Compression	Shear
≥ 3,5 mm	≥ 2,0 mm	≥ 2,0 mm
≥ 3,0 mm	≥ 1,5 mm	≥ 1,5 mm
≥ 2,0 mm	≥ 1,5 mm	≥ 1,0 mm

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de