



KEIM Stucasol

DECLARATION OF PERFORMANCE

Number of the declaration of performance and definite identification code of the product type:
03 0013

Intended use

Render with organic binders to be used as exterior and interior coating for walls, ceilings, pillars and partition walls

Manufacturer

KEIMFARBEN GMBH, Keimstraße 16, 86420 Diedorf, Germany

System for evaluation and verification of performance constancy
System 3

Harmonized standard
EN 15824:2009

Notified body (testing institute)

MPA Braunschweig (0761-CPD)

performed the product type test regarding the fire behaviour according to system 3.

Declared performance

Significant characteristics	Performance
Water vapour permeability	V1
Water absorption	W3
Adhesion strength	≥ 0.3 MPa
Durability (frost-resistance)	Permeability rate as per EN 1062-3: ≤ 0.5 kg/(m ² h ^{0.5})
Thermal conductivity	NPD
Fire behaviour	A2-s1,d0
Hazardous substances	NPD

The performance of the product for which this declaration of performance was issued conforms to the declared performance.

The manufacturer stated in this declaration of performance bears sole responsibility for the preparation of this performance declaration in accordance with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer:

Peter Jaser, Head of Quality Assurance and Colorimetry

Diedorf, 25.08.2015

p.p. Peter Jaser

Appendix Material Safety Data Sheet

Keimstraße 16 / 86420 Diedorf
Tel. +49 (0)821 4802-0
Fax +49(0)821 4802-210

Frederik-Ipsen-Straße 6 / 15926 Luckau
Tel. +49(0) 35456 676-0
Fax +49(0) 35456 676-38

www.keimfarben.de
info@keimfarben.de

Deutsche Bank München
IBAN DE37 7007 0010 0188 1580 00
BIC DEUTDE33

Stadtparkasse Augsburg
IBAN DE48 7205 0000 0000 3621 03
BIC AUGSDE33

Registergericht Augsburg HRB 27263
Geschäftsführer: Rüdiger Lugert