



TECHNICAL DATA SHEET

KEIM ANPUTZLEISTE W35-PRO BLACK

1. PRODUCT DESCRIPTION

Connection profile as plastering and sealing strip with fabric, integrated telescopic mechanism for three-dimensional movement absorption and plaster removal edge. Foldable protective flap for cover foil.

2. FIELD OF APPLICATION

For durable and driving rain-proof connection joints between frame or door frame and ETICS. The movements from the component and the ETICS are absorbed.

Suitable for window and door reveals.

Further instructions for use in the KEIM detailed plans.

3. PRODUCT PROPERTIES

- universally applicable
- fire behaviour: hardly inflammable B1 according to 4102
- protects against ingress of water in liquid form
- permeable
- resistant to aging

MATERIAL CHARACTERISTICS:

- Proven driving rain tightness, max. wind pressure: min. 600 Pa
- Fabric flag mesh width: 4 x 4 mm
- Fabric flag width: ca. 12,5 cm
- maximum insulation thickness: 300 mm
- Thicker insulation thickness: on request
- max. window size: 10 m²
- Larger windows: on request
- Colour shade: anthracite

PERFORMANCE AND CRITERIAS OF SELECTION:

- Eignung: für alle Farbkombinationen von Rahmen und Putzen geeignet
- Visible joints: Shadow gap
- Space requirement on the frame (incl. protective flap): 10 mm (25 mm)

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Clean the frame. The frame must be dry, clean, even and free of adhesion-reducing layers. Before using adhesive profiles, an adhesive test is required. For this, clean a hidden area with a dry and clean tissue (without cleaning agents). Stick profile section (ca. 10 cm) and press firmly. After waiting for approx. 10 minutes, slowly remove the profile from the substrate. For an adhesive suitability the foam tape must stick to both surfaces (profile and substrate) = complete foam break. On critical substrates, e.g.: plastic windows, oiled or varnished wooden windows, powder or teflon coated metallic windows, the leakage of waxes, oils and plasticisers can never be fully excluded.

TECHNICAL DATA SHEET – KEIM ANPUTZLEISTE W35-PRO BLACK

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying from min. 5 °C to max. 30 °C. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

APPLICATION:

Cut to size with anvil shears or suitable angle sander.

KEIM Anputzleiste W35-Pro Black is to be applied before the application of the base coat.

If possible, attach the profiles just before gluing the insulation panels or just before starting the reinforcement. First glue the profile to the lintel area (horizontal), then the side profiles (vertical). Release protection brackets in the joint area (lintel/reveal). The profiles may also be mitred and mounted. Joint sealing tape must be used in the joint area between lintel and reveal as well as between profile sections. Press profiles on well. Cutting the profiles from the back prevents premature activation of the protective mechanisms. Apply the system's reinforcing mortar at the appropriate points and embed KEIM Anputzleiste W35-Pro Black centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

5. DELIVERY FORM

Product name	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
Anputzleiste W 35-Pro Black	2.40	25	60	carton

DELIVERY FORM ADDITIONAL INFORMATION

Delivery in cartons

6. STORAGE

Storage conditions
flat-lying in the outer cardboard avoid deflection dry frost-free

STORAGE INFORMATION

Observe the instruction leaflet in the packaging!

7. DISPOSAL

EC WASTE CODE:

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

9. GENERAL INFORMATION

TECHNICAL DATA SHEET – KEIM ANPUTZLEISTE W35-PRO BLACK

CLASSIFICATION OF THE SEALING STRIP AFTER ITS MOVEMENT ABSORPTION

Elongation	Compression	Shear
≥ 3,5 mm	≥ 2,0 mm	≥ 2,0 mm
≥ 3,0 mm	≥ 1,5 mm	≥ 1,5 mm
≥ 2,0 mm	≥ 1,5 mm	≥ 1,0 mm

WINDOW POSITION AND WINDOW DIMENSION

maximum insulation thickness	max. window size
≤ 300 mm	≤ 6 m ²
≤ 300 mm	≤ 10 m ²
≤ 300 mm	≤ 2,6 m ²
≤ 160 mm	≤ 6 m ²
≤ 300 mm	≤ 10 m ²
≤ 300 mm	≤ 10 m ²

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.