



## TECHNICAL DATA SHEET

# APU-GEWEBELEISTE ROMA W31

## 1. PRODUCT DESCRIPTION

---

Connecting profile as a fitting and sealing strip with fabric, Sk-PE sealing tape and TPE loop.

## 2. FIELD OF APPLICATION

---

For permanent and driving rain-proof connection joints for lateral connections to front-mounted roller shutter systems or roller shutter guide rails. The movements from the component and the ETICS are absorbed.

Suitable for window and door reveals.

Further information on application in the KEIM detailed plans.

## 3. PRODUCT PROPERTIES

---

- fire behaviour: hardly inflammable B1 according to 4102
- protects against ingress of water in liquid form
- permeable
- resistant to aging

### MATERIAL CHARACTERISTICS:

- Proven driving rain tightness, max. wind pressure: min. 600 Pa
- Fabric flag mesh width: 4 x 4 mm
- Fabric flag width: ca. 12,5 cm
- maximum insulation thickness: 300 mm
- Thicker insulation thickness: on request
- max. window size: 10 m<sup>2</sup>
- Larger windows: on request
- Colour shade: white

### PERFORMANCE AND CRITERIAS OF SELECTION:

- Eignung: für helle Rahmen und hellen Putz für helle Rahmen und dunklen Putz oder umgekehrt
- Visible joints: Foam tape white
- Space requirement on the frame (incl. protective flap): 14 mm (23 mm)

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

Clean the frame. The frame must be dry, clean, even and free of adhesion-reducing layers. Before using adhesive profiles, an adhesive test is required. For this, clean a hidden area with a dry and clean tissue (without cleaning agents). Stick profile section (ca. 10 cm) and press firmly. After waiting for approx. 10 minutes, slowly remove the profile from the substrate. For an adhesive suitability the foam tape must stick to both surfaces (profile and substrate) = complete foam break. On critical substrates, e.g.: plastic windows, oiled or varnished wooden windows, powder or teflon coated metallic windows, the leakage of waxes, oils and plasticisers can never be fully excluded.

## TECHNICAL DATA SHEET – APU-GEWEBELEISTE ROMA W31

### APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying from min. 5 °C to max. 30 °C. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

### CONSUMPTION:

approx. 1,1 m/m

### APPLICATION:

Cut to size with anvil shears or suitable angle sander.

If possible, attach the profiles just before gluing the insulation panels or just before starting the reinforcement. First glue the profile to the lintel area (horizontal), then the side profiles (vertical). Release protection brackets in the joint area (lintel/reveal). The profiles may also be mitred and mounted. Joint sealing tape must be used in the joint area between lintel and reveal as well as between profile sections. Press profiles on well.

### AFTERTREATMENT:

After the finish paint coat the protective flashing of APU-Gewebeleiste Roma W31 is snapped off and removed.

## 5. DELIVERY FORM

Product name	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
Anputzleiste Roma W31	2.40	25	60	carton

### DELIVERY FORM ADDITIONAL INFORMATION

Delivery in cartons, delivery form in pieces on request. Alternative plastering strip with integrated joint sealing tape (class A) on request.

## 6. STORAGE

Storage conditions
flat-lying in the outer cardboard avoid deflection dry frost-free

### STORAGE INFORMATION

Observe the instruction leaflet in the packaging!

## 7. DISPOSAL

### EC WASTE CODE:

Waste code: 17 09 04

## 8. SAFETY INSTRUCTIONS

No particular indications.

## 9. GENERAL INFORMATION

## TECHNICAL DATA SHEET – APU-GEWEBELEISTE ROMA W31

### CLASSIFICATION OF THE SEALING STRIP AFTER ITS MOVEMENT ABSORPTION

Elongation	Compression	Shear
≥ 3,5 mm	≥ 2,0 mm	≥ 2,0 mm
≥ 3,0 mm	≥ 1,5 mm	≥ 1,5 mm
≥ 2,0 mm	≥ 1,5 mm	≥ 1,0 mm

### WINDOW POSITION AND WINDOW DIMENSION

maximum insulation thickness	max. window size
≤ 300 mm	≤ 6 m <sup>2</sup>
≤ 300 mm	≤ 10 m <sup>2</sup>
≤ 300 mm	≤ 2,6 m <sup>2</sup>
≤ 160 mm	≤ 6 m <sup>2</sup>
≤ 300 mm	≤ 10 m <sup>2</sup>
≤ 300 mm	≤ 10 m <sup>2</sup>

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.