



TECHNICAL DATA SHEET

KEIM DACHBELÜFTUNGSPROFIL

1. PRODUCT DESCRIPTION

End profile made of coated aluminium, with perforated leg.

2. FIELD OF APPLICATION

For mounting on insulation boards, for DIN-compliant roof ventilation of cold roofs.

3. PRODUCT PROPERTIES

- easy to use
- suitable for all insulation panel thicknesses and kinds
- fire behaviour: non-flammable

MATERIAL CHARACTERISTICS:

- Ventilation cross-section: 207 cm²/m
- Colour shade: white

4. APPLICATION INSTRUCTIONS

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be in the range between max. 5 °C and max. 30 °C.

APPLICATION:

Cut to size with anvil shears or suitable angle sander.

KEIM Dachbelüftungsprofil is to be applied before the application of the base coat.

REINFORCEMENT:

Apply the system's reinforcing mortar at the appropriate points and embed KEIM Dachbelüftungsprofil centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

AFTERTREATMENT:

After complete drying of the base coat, the surface is reinforced.

5. LIEFERFORM

Product name	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
Dachbelüftungsprofil	2.50	20	50	carton

LIEFERFORM

Delivery in cartons

TECHNICAL DATA SHEET – KEIM DACHBELÜFTUNGSPROFIL

6. LAGERUNG

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering flat-lying in the outer cardboard

7. ENTSORGUNG

ENTSORGUNG

Waste code: 17 09 04

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de