



TECHNICAL DATA SHEET

EJOT® DDT

1. PRODUCT DESCRIPTION

Combination plate made of metal only in combination with ejot DDS-z, with European Technical Approval (ETA): Z-21.8-1980

2. FIELD OF APPLICATION

In combination with ejot DDS-z for secure fixing of ceiling and acoustic insulation in cracked and non-cracked concrete, Recommended anchoring base: Concrete

3. PRODUCT PROPERTIES

- easy and fast processing
- fire behaviour: non-flammable

MATERIAL CHARACTERISTICS:

- Colour shade: white

4. APPLICATION INSTRUCTIONS

APPLICATION:

For processing instructions, please refer to the Ejot DDS-z technical data sheet.

5. LIEFERFORM

LIEFERFORM

Product name	Plate diameter	Pieces per unit	Type of container
Ejot DDT	mind. 70 mm	100	carton
Ejot DDS-z		100	carton

6. LAGERUNG

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering

7. ENTSORGUNG

ENTSORGUNG

Waste code: 17 09 04

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.