



## TECHNICAL DATA SHEET

# KEIM FENSTERBANKHALTER

## 1. PRODUCT DESCRIPTION

---

Aluminium window sill bracket, sizes 1 to 8.

## 2. FIELD OF APPLICATION

---

For anchoring the window sill to the underside of the masonry during previous installation.

## 3. PRODUCT PROPERTIES

---

- easy to use
- easy and fast processing
- With elongated holes for better alignment
- both sides coated, applicable without pressing technique
- fire behaviour: non-flammable

### MATERIAL CHARACTERISTICS:

- Ausladung: siehe Tabelle Lieferform
- Colour shade: naturally anodized

## 4. APPLICATION INSTRUCTIONS

---

### APPLICATION:

The window sill holder is used to stabilise the window sill on the wall during previous installation. For this purpose, after the window sill has been installed, the cranked, front part of the assembled window sill holder, which matches the size, is hooked into the drip edge groove of the window sill. Then the extendable and variable projection mounting part with the slotted hole is fixed precisely to the substrate (with 2 screws each, e.g. impact dowel ND K).

From a projection of 150 mm, window sill brackets must be installed at a distance of max. 60 cm. The lateral distance to the end caps must not exceed 40 cm on the right and left.

The installation of window sill brackets is not required for retrofitting.

## TECHNICAL DATA SHEET – KEIM FENSTERBANKHALTER

### 5. DELIVERY FORM

Product name	Ausladung	Inhalt je VE	Type of container
Fensterbankhalter Größe 1	90 - 110 mm	1	set
Fensterbankhalter Größe 2	110 - 140 mm	1	set
Fensterbankhalter Größe 3	140 - 180 mm	1	set
Fensterbankhalter Größe 4	180 - 240 mm	1	set
Fensterbankhalter Größe 5	200 - 260 mm	1	set
Fensterbankhalter Größe 6	240 - 300 mm	1	set
Fensterbankhalter Größe 7	280 - 340 mm	1	set
Fensterbankhalter Größe 8	340 - 400 mm	1	set

### RELATED PRODUCTS

Product name	Dowel diameter	Length [m]	Pieces per unit	Type of container
Schlagdübel ND K 6 x 60	6 mm	0.06	100	carton
Schlagdübel ND K 8 x 80	8 mm	0.08	100	carton

### 6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry

### 7. DISPOSAL

#### EC WASTE CODE:

Waste code: 17 04 02

### 8. SAFETY INSTRUCTIONS

No particular indications.

### 9. GENERAL INFORMATION

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.