



TECHNICAL DATA SHEET

KEIM REVERFIX

1. PRODUCT DESCRIPTION

KEIM Reverfix is a removable fixing and thinning agent in the KEIM Reversil system.

2. FIELD OF APPLICATION

With KEIM Reverfix, highly absorbent or gypsum-containing substrates can be primed before painting with the KEIM Reversil system and thus reduced in their absorbency. Chalking substrates can be strengthened with a primer with KEIM Reverfix. For the production of glaze coats or glazed paintings, KEIM Reversil can be diluted with KEIM Reverfix up to the desired glaze effect. KEIM Reverfix like KEIM Reversil, can later be removed with water without damaging or distorting the substrate.

3. PRODUCT PROPERTIES

- reversible
- smudge-proof
- solidifying
- highly permeable

MATERIAL CHARACTERISTICS:

- Density: approx. 1.0 - 1.1 g/cm³
- pH value: approx. 8

COLOUR SHADES:

milky

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

The substrate must be sound, solid, dry, clean and free from dust and grease.

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be ≥ 5 °C.

PREPARATION OF MATERIAL:

CONSUMPTION:

approx. 0,2 L/m² for a single coating.

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

APPLICATION:

For priming highly absorbent, gypsum-containing or chalking substrates, apply undiluted with a brush or paintbrush.

Removal:

Pre-wet thoroughly with water and then wash off with clear water and a brush after approx. 10 minutes exposure time.

CLEANING OF TOOLS:

Clean immediately with water.

TECHNICAL DATA SHEET – KEIM REVERFIX

5. PACKAGING

| Container content | Unit of measure | Quantity on pallet | Type of container |
|-------------------|-----------------|--------------------|-------------------|
| 20 | L | 24 | jerry can |
| 5 | L | 96 | jerry can |

6. STORAGE

| max. storage time | Storage conditions |
|-------------------|---|
| 6 months | cool frost-free keep container tightly sealed. protected from heat and direct sun. |

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 08 01 12

8. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet. EU limit value for this product (Cat. A/h): 30 g/l.
This product contains: 0 - 1 g/l VOC.

9. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.
Mixing with products not part of the system or other foreign additives is not permitted.

10. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.