



## TECHNICAL DATA SHEET

# KEIM SANIERFRÄSER

## 1. PRODUCT DESCRIPTION

---

Metal renovation cutter (Ø 60 mm).

## 2. FIELD OF APPLICATION

---

For recessed installation of plate anchors when renovating ETICS facades.

## 3. PRODUCT PROPERTIES

---

- easy to use
- especially economical
- Robust design for long service life
- Quickly replaceable wear parts
- long-lasting

### MATERIAL CHARACTERISTICS:

- Colour shade: grey

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

Drill the hole at right angles to the surface of the anchoring base.  
The drill hole must be at least 10 mm deeper than the minimum anchorage depth.  
Remove drill dust from the drill hole.

### APPLICATION:

Milling of the existing plaster layer with the KEIM Sanierfräser in the area of the drill holes. Installation of the screw anchor to be inserted with the aid of the associated setting tool.

### REINFORCEMENT:

After inserting a STR roundel flush with the surface to create a level plaster base, the reinforcement and finishing plaster are applied in the desired KEIM plaster system.

## 5. DELIVERY FORM

---

Product name	Plate diameter	Inhalt je VE	Type of container
Sanierfräser	für 60 mm geeignet	1	piece

## TECHNICAL DATA SHEET – KEIM SANIERFRÄSER

---

### 6. STORAGE

---

max. storage time	Storage conditions
no maximum storage time	flat-lying in the outer cardboard

### 7. DISPOSAL

---

No special notes.  
Waste metals

### 8. SAFETY INSTRUCTIONS

---

no particular indications

### 9. GENERAL INFORMATION

---

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210  
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38  
www.keim.com / info@keimfarben.de