



TECHNICAL DATA SHEET

POLYCHRO-FOND

1. PRODUCT DESCRIPTION

polyChro-fond ist ein diffusionsoffenes, mineralisches Grundiermittel für innen.

2. FIELD OF APPLICATION

polyChro-fond dient zur Vorbehandlung von Innenflächen, die nachfolgend mit der echten Le Corbusier-Innenwandfarbe „polyChro-intérieur“ gestrichen werden. polyChro-fond wird angewendet

- zur Egalisierung von eventuellen Unterschieden in der Saugfähigkeit bei mineralischen und/oder organischen Untergründen bzw. tragfähigen Altbeschichtungen.
- zur Verfestigung von stark saugenden, kreidenden oder sandenden Untergründen.

Durch die Grundierung mit polyChro-fond lässt sich Oberflächenhomogenität von Anstrichen optimieren. Dies gilt insbesondere bei schwierigen Lichtverhältnissen wie Streiflicht.

3. PRODUCT PROPERTIES

- absorption-regulating
- equalising
- solidifying
- adhesion-promoting
- permeable
- microporous
- no solvents added
- low-odour

MATERIAL CHARACTERISTICS:

- Density: ca. 1,0 - 1.1 g/cm³
- Organic content: < 5 %

4. APPLICATION INSTRUCTIONS

CONSUMPTION:

approx. 0,1 - 0,2 l/m²

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

CLEANING OF TOOLS:

Clean immediately with water.

TECHNICAL DATA SHEET – POLYCHRO-FOND

5. PACKAGING

Container content	Unit of measure	Quantity on pallet	Type of container
5	l	96	jerry can

6. STORAGE

max. storage time	Storage conditions
12 months	frost-free cool protected from heat and direct sun.

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

EC WASTE CODE:

Waste code: 08 01 11 *

8. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet.

GISCODE:

GIS code: BSW 50

9. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

10. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de