

Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022

Version number 14.0 (replaces version 13.0)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture

Mineral coating grout for vertical sealing of structures, both exterior and interior.

- · Uses advised against All other uses are not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood GB-Telford, Shropshire TF2 7NA

Tel +44 1952 231 250 / Fax +44 1952 231 251 www.keim.com / sales@keimpaints.co.uk

· Further information obtainable from:

**David Pratt** 

Telefon: +44 1952 231250
E-Mail: sales@keimpaints.co.uk

1.4 Emergency telephone number:
GBK GmbH Global Regulatory Compliance
Emergency number: +49(0)6132/84463

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cement, portland, chemicals

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

(Contd. on page 2)

Revision: 27.09.2022



Page 2/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

#### Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 1)

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection.

P261 Avoid breathing dust.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P315 Get immediate medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P362 Take off contaminated clothing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

· 2.3 Other hazards

This Product contains cement. Cement produces an alkaline reaction with moisture or water. Avoid contact with eyes and prolonged skin contact.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable · **vPvB:** Not applicable

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Portland-cement, aggregate and additives

#### Dangerous components:

· Additional information:

The cement used is low in chromate, as its content of soluble chromium (VI) is below 2 ppm (0.0002%).

For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: When seeing the doctor we suggest to present this safety data sheet.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not use solvents or thinners.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse mouth and throat well with water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Special protective equipment: Wear self-contained respiratory protective device.
- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. In case of fire do not breathe smoke, fumes and vapours.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Avoid formation of dust.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Respect the protection rules (see section 7 and 8).

Product forms slippery surface when combined with water.

6.2 Environmental precautions:

Do not allow product to reach soil, sewage system or any water course.

Follow local governmental rules and regulations.

6.3 Methods and material for containment and cleaning up:

Close drainages (risk of blocking)

Danger of slipping!

Avoid formation of dust.

Ensure adequate ventilation.

Pick up mechanically.

Dispose of the material collected according to regulations.

Clear contaminated areas thoroughly.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Avoid contact with skin and eves.

Keep receptacles tightly sealed.

(Contd. on page 4)



Page 4/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

#### Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 3)

Prevent formation of dust.

Any unavoidable deposit of dust must be regularly removed.

Ensure good ventilation/exhaustion at the workplace.

See item 8 (8.2) for information about suitable protective equipment and technical precautions. Respect the protection rules.

Information about fire - and explosion protection:

The product is not flammable.

No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Keep in the original containers in a cool and dry place.

Store only in unopened original receptacles.

- Information about storage in one common storage facility: Do not store together with acids.
- · Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

Avoid dust formations and deposits.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 13
- · 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

General dust limit (Germany): Long-term value: 1.25 \* 10 \*\* mg / m³ 2 (II);

\* respirable fraction \*\* inhalable fraction
The national general dust limit value must be observed.

#### 65997-15-1 Cement, portland, chemicals

WEL Long-term value: 10\* 4\*\* mg/m³ \*inhalable dust \*\*respirable dust

**DNELs** 

#### 65997-15-1 Cement, portland, chemicals

Inhalative | Long-term - systemic effects | 1 mg/m³ (worker)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Avoid contact with the eyes and skin.

Do not inhale dust / smoke / mist.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)



Page 5/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 4)

#### · Respiratory protection:

In a dusty environment wear suitable facemask.

Filter: FFP2

#### · Hand protection

Protective gloves

Alkaline resistant gloves

#### · Material of gloves

suitable material e.g.:

Nitrile impregnated cotton-gloves

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Value for the permeation: level  $\geq$  6 (480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye/face protection

In a dusty environment wear protective goggles.

Tightly sealed goggles

#### · Body protection:

Protective work clothing

After contact with skin wash thoroughly with water and apply lotion.

### Environmental exposure controls

See Section 12 and 6.2

No further relevant information available.

#### **SECTION 9: Physical and chemical properties**

## $\cdot$ 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odourless
Odour threshold:
Melting point/freezing point:

Solid
Grey
Odourless
Not determined
Not determined

Boiling point or initial boiling point and

boiling range Not applicable. Flammability Not applicable

· Lower and upper explosion limit

· Lower: Not applicable · Upper: Not applicable

(Contd. on page 6)



Page 6/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 5) · Flash point: Not applicable · Ignition temperature: Not determined Decomposition temperature: Not determined · pH at 20 °C 11.5-13.5\* mixed with water · Viscosity: Kinematic viscosity Not applicable · Dynamic: Not applicable · Solubility · water: Miscible Partition coefficient n-octanol/water (log value) Not applicable · Vapour pressure: Not applicable. Density and/or relative density · Density: Not determined · Relative density Not determined · Bulk density: 1.300-1.500\* kg/m3 · Vapour density Not applicable. \* The values are for freshly produced material · 9.2 Other information and may change with the time. · Appearance: Powder · Form: · Important information on protection of health and environment, and on safety. **Auto-ignition temperature:** Product is not selfigniting. · Explosive properties: Product does not present an explosion hazard. · Change in condition · Softening point/range · Oxidising properties: Not applicable · Evaporation rate Not applicable · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void

(Contd. on page 7)



Page 7/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

Contd.	of	nage	6
COLITY.	UI	paye	v

		(Conta. or page o
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity Reacts with water alkaline and hardens.
- · 10.2 Chemical stability Stable under normal conditions of storage and use.
- Thermal decomposition / conditions to be avoided:

Stable at environment temperature.

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Humidity
- · 10.5 Incompatible materials: Acids
- · 10.6 Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed.

### **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50 values relevant for classification:				
65997-15-	1 Cement	, portland, chemicals		
Dermal	LD50	>2,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>5 mg/l (rat)		

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · during inhalation: Irritating to respiratory system.
- · during swallowing: Irritant effect possible
- · Respiratory or skin sensitisation

Product is reduced in chromate. Within the indicated storage time sensitization is not expected.

- · STOT-single exposure May cause respiratory irritation.
- Other information (about experimental toxicology):

Experimental analysis are not available.

The product was not tested. The statements on toxicology have been derived from the properties of the individual components.

- · Subacute to chronic toxicity:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Not applicable

(Contd. on page 8)



Page 8/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 7)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable
- · **vPvB**: Not applicable
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · AOX-indication:

According to our standard of knowledge the product does not contain any organic bounded halogen. The product has no influence on the waste water's AOX-value.

According to the formulation contains the following heavy metals and compounds from the EU quideline NO. 2006/11/EC:

According to our current data base the product does not consist of any heavy metals or substances of EU-directives 76/464/EWG.

General notes:

At present there are no ecotoxicological assessments.

The statements on ecotoxicology have been derived from the properties of the individual components.

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Disposal must be made according to official regulations.

Must not be disposed with household garbage. Do not allow product to reach sewage system.

Unused remainders of the product should be regarded as hazardous waste.

Recommendation for non-reusable residues: Mix with water and allow to harden.

Allow wet product and product sludge to harden and do not allow to get into drains or waterways.

· European waste catalogue

17 01 01 | concrete

(Contd. on page 9)



Page 9/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 8)

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Non contaminated packagings may be recycled.

· Recommended cleansing agents: Water, if necessary with cleansing agents.

SECTION 14: Transport informat	tion	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable	
· 14.7 Maritime transport in bulk accordi IMO instruments	ng to Not applicable	
· Transport/Additional information:	No dangerous good in sense of these transporegulations.	
UN "Model Regulation":	Void	

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

For information on labelling please refer to section 2 of this document.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)



Page 10/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.09.2022 Version number 14.0 (replaces version 13.0) Revision: 27.09.2022

Trade name: KEIM POROSAN-DICHTUNGSSCHLÄMME

(Contd. of page 9)

- · Other regulations, limitations and prohibitive regulations
- · Please note:

TRGS 200 (Germany)

TRGS 500 (Germany)

TRGS 510 (Germany)

TRGS 900 (Germany)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

- · Department issuing SDS: KEIMFARBEN Germany, Product safety department
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

EC10: Effective concentration at 10% mortality rate.

EC50: Half maximal effective concentration.

LC10: Lethal concentration at 10% mortality rate.

NOEC: No observed effect concentration.

UK REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.