



TECHNICAL DATA SHEET

KEIM PVC-SOCKELEINSTECKPROFIL

1. PRODUCT DESCRIPTION

Base insertion profile made of rigid PVC with fixed fabric flag, can be used individually or in conjunction with PVC base profile.

2. FIELD OF APPLICATION

For the creation of a thermal bridge-free, variable, as well as sufficiently tight and dimensionally stable system termination in the base area,

- by mounting on the substrate in combination with base and base insertion profile, for insulation thicknesses from 60 mm to 240 mm or
- by subsequent insertion of the base insertion profile between the layers of base and facade insulation, before reinforcing and without limitation of the insulation thickness (base insulation with setback 20 - 40 mm).

3. PRODUCT PROPERTIES

- especially economical
- easy and fast processing
- suitable for all insulation panel thicknesses and kinds
- with fixed fabric flag
- with integrated drip edge
- With elongated holes for better alignment
- non-slip
- thermal bridge free
- alkali-resistant
- resistant to aging

MATERIAL CHARACTERISTICS:

- Mesh size: 4 x 4 mm
- Length: 2,00 m
- Colour shade: white

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

The substrate must be strong, dry, clean, sound and free from adhesion-reducing residues. Unevenness of up to 1 cm/m may be bridged. Larger unevenness must be mechanically levelled or by applying a render in accordance with DIN EN 998-1.

CONSUMPTION:

approx. 1,0 m/m

APPLICATION:

After the insulation panels have been installed, insert the plug-in profiles into the opening of the PVC plinth profile or between the plinth and facade insulation without joints, butt-jointed, aligned and offset (≥ 300 mm).

TECHNICAL DATA SHEET – KEIM PVC-SOCKELEINSTECKPROFIL

5. PACKAGING

Product name	Panel thickness [mm]	Length [m]	Pieces per unit	Content per sold unit [m]	Type of container
PVC- Sockeleinsteckprofil 60 - 90 mm	60 - 90	2.00	10	20.00	carton
PVC- Sockeleinsteckprofil 100 - 240 mm	100 - 240	2.00	10	20.00	carton

RELATED PRODUCTS

Product name	Panel thickness	Length [m]	Pieces per unit	Content per sold unit [m]	Type of container
PVC- Sockelgrundprofil 60 - 90 mm	60 - 90	2.00	10	20.00	carton
PVC- Sockelgrundprofil 100 - 160 mm	100 - 160	2.00	10	20.00	carton
PVC- Sockelgrundprofil 180 - 240 mm	180 - 240	2.00	10	20.00	carton
Distanzstücke	3, 5, 8, 10, 15		100		carton

Delivery in cartons

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	even avoid deflection

7. DISPOSAL

Waste code: 17 09 04

8. SAFETY INSTRUCTIONS

No particular indications.

TECHNICAL DATA SHEET – KEIM PVC-SOCKELEINSTECKPROFIL

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood / Telford / Shropshire TF2 7NA
Tel. +44 1952 231 250 / Fax +44 1952 231 251
www.keim.com / sales@keimpaints.co.uk