



TECHNICAL DATA SHEET

KEIM STR-RONDELLE

1. PRODUCT DESCRIPTION

<https://www.ejot.de/Baubefestigungen/Anwendungen/WDVS-Befestigungsloesungen/FBCr-D%3%A4mmstoffplatten/ejothem%2%AE-STR-Rondelle-EPS/p/STR-cap-EPS>

2. FIELD OF APPLICATION

<https://www.ejot.de/Baubefestigungen/Anwendungen/WDVS-Befestigungsloesungen/FBCr-D%3%A4mmstoffplatten/ejothem%2%AE-STR-Stopfen/p/STR-plug>

3. PRODUCT PROPERTIES

- ready to use
- easy and fast processing

MATERIAL CHARACTERISTICS:

- Colour shade: assorted colours

4. APPLICATION INSTRUCTIONS

APPLICATION:

After recessed installation, the anchor plate must be covered with Ejothem STR-Rondelle MW/EPS-grey, after surface-flush installation, the anchor shaft must be closed with the Ejot STR plug.

5. PACKAGING

Product name	Pieces per unit	Type of container
STR-Rondelle-MW	100	carton
STR-Rondelle-EPS grau	100	carton

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry

7. DISPOSAL

No special notes.

Waste code:

8. SAFETY INSTRUCTIONS

No particular indications.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

