

KEIM STEINREINIGER-N

1. PRODUCT DESCPRIPTION

Neutral cleaning concentrate on an aqueous basis

2. FIELD OF APPLICATION

KEIM Steinreiniger-N is a cleaning concentrate adapted to the requirements of steam-blasting equipment. Due to its wide range of applications, KEIM Steinreiniger-N is suitable for universal use, especially for mild and gentle cleaning of stubborn dust, grease, oil and soot stains on natural stone, concrete and clinker facades.

3. PRODUCT PROPERTIES

- universally applicable
- aqueous

MATERIAL CHARACTERISTICS:

- Density:
- pH value:

approx. 1,0 - 1.1 g/cm³ approx. 7,1

COLOUR SHADES:

yellow-brown

4. APPLICATION INSTRUCTIONS

CONSUMPTION:

Determine consumption on the basis of sample surfaces.

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

APPLICATION:

Precoat atmospherically soiled surfaces with Steinreiniger-N, diluted 1:10 with Water. After an exposure time of at least 1 hour, remove soiling from the bottom to the top using water pressure jetting (hot or cold).

Or KEIM Steinreiniger-N, diluted 1:10 with Water, add to the dosing container of the steam jet unit. Then clean soiled surfaces from bottom to top using the water pressure jet method. Afterwards, the cleaned surfaces must be rinsed with clear Water.

Note: Not suitable for removing crusty soiling.

DRYING TIME:

CLEANING OF TOOLS:

Clean immediately with water.

5. PACKAGING

Container content	Unit of measure	Type of container
10	kg	jerry can

6. STORAGE

max. storage time	Storage conditions
12 months	frost-free keep container tightly sealed.

7. DISPOSAL

For disposal information refer to section 13 of the safety data sheet.

Waste code: 07 06 99

8. SAFETY INSTRUCTIONS

Please, refer to the Material Safety Data Sheet. EU limit value for this product . This product contains: - g/l VOC.

9. GENERAL INFORMATION

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

10. CERTIFICATES & QUALITY SEALS



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.

