

Page 1/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: KEIM UNIPUTZ 1.3
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture

Dry mortar to be mixed with water and then used as a plaster for walls and ceilings indoors and outdoors.

Renovation and thin layer exterior wall render, based on lime cement with a small amount of organic additives and fibre reinforcement.

- · Uses advised against All other uses are not recommended.
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

KEIM MINERAL PAINTS LTD

Santok Building / Deer Park Way, Donnington Wood GB-Telford, Shropshire TF2 7NA Tel +44 1952 231 250 / Fax +44 1952 231 251 www.keim.com / sales@keimpaints.co.uk

· Further information obtainable from:

David Pratt

Telefon: +44 1952 231250
E-Mail: sales@keimpaints.co.uk

1.4 Emergency telephone number:
GBK GmbH Global Regulatory Compliance
Emergency number: +49(0)6132/84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Cement, portland, chemicals calcium dihydroxide

(Contd. on page 2)



Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection.

P261 Avoid breathing dust.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P315 Get immediate medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P362 Take off contaminated clothing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

· 2.3 Other hazards

This Product contains cement. Cement produces an alkaline reaction with moisture or water. Avoid contact with eyes and prolonged skin contact.

- · Results of PBT and vPvB assessment
- PBT: Not applicablevPvB: Not applicable

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Portland-cement, calcium dihydroxide, aggregates and additives

· Dangerous components:		
CAS: 65997-15-1 EINECS: 266-043-4	Cement, portland, chemicals	10-25%
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45- XXXX	calcium dihydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	2.5-10%

· Additional information:

The cement used is low in chromate, as its content of soluble chromium (VI) is below 2 ppm (0.0002%).

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: When seeing the doctor we suggest to present this safety data sheet.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



Page 3/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 2)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Do not use solvents or thinners.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse mouth and throat well with water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Product itself does not burn. Co-ordinate fire-fighting measures to the fire surroundings.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Special protective equipment: Wear self-contained respiratory protective device.
- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

In case of fire do not breathe smoke, fumes and vapours.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Avoid formation of dust.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Respect the protection rules (see section 7 and 8).

Product forms slippery surface when combined with water.

6.2 Environmental precautions:

Do not allow product to reach soil, sewage system or any water course.

Follow local governmental rules and regulations.

6.3 Methods and material for containment and cleaning up:

Close drainages (risk of blocking)

Danger of slipping!

Avoid formation of dust.

Ensure adequate ventilation.

Pick up mechanically.

Dispose of the material collected according to regulations.

Clear contaminated areas thoroughly.

(Contd. on page 4)



Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Keep receptacles tightly sealed.

Prevent formation of dust.

Ensure good ventilation/exhaustion at the workplace.

Any unavoidable deposit of dust must be regularly removed.

See item 8 (8.2) for information about suitable protective equipment and technical precautions. Respect the protection rules.

· Information about fire - and explosion protection:

The product is not flammable.

No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Keep in the original containers in a cool and dry place.

Store only in unopened original receptacles.

- Information about storage in one common storage facility: Do not store together with acids.
- Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

Avoid dust formations and deposits.

Keep container tightly sealed.

Protect from heat and direct sunlight.

- · Storage class: 13
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with	limit values that	require monitorin	g at the workplace:

65997-15-1 Cement, portland, chemicals

WEL Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust

1305-62-0 calcium dihydroxide

WEL Short-term value: 4* mg/m³ Long-term value: 5 1* mg/m³

*resprable fraction

(Contd. on page 5)



Page 5/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

		(Contd. of pa
DNELs		
1305-62-0	calcium dihydroxide	
Inhalative	Acute - local effects	4 mg/m³ (consumer) respirable dust
		4 mg/m³ (worker) respirable dust
	Long-term - local effects	1 mg/m³ (consumer) respirable dust
		1 mg/m³ (worker) respirable dust
PNECs		
1305-62-0	calcium dihydroxide	
Aquatic compartment - freshwater		0.49 mg/l (Freshwater)
Aquatic compartment - marine water		r 0.32 mg/l (Seawater)
Terrestria	l compartment - soil	1,080 mg/kg dw (soil)
Sewage treatment plant		3 mg/l (Microorganism)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Vacuum clean contaminated clothing. Do not blow or brush off contamination.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not inhale dust / smoke / mist.

· Respiratory protection:

In a dusty environment wear suitable facemask.

Filter: FFP2

· Hand protection

Protective gloves

Alkaline resistant gloves

· Material of gloves

suitable material e.g.:

Nitrile impregnated cotton-gloves

Recommended thickness of the material: > 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Value for the permeation: level \geq 6 (480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 6)



Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 5)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

In a dusty environment wear protective goggles.

Tightly sealed goggles

· Body protection:

Protective work clothing

After contact with skin wash thoroughly with water and apply lotion.

· Environmental exposure controls

See Section 12 and 6.2

No further relevant information available.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odourless
Odour threshold:
Melting point/freezing point:
Not determined
Not determined

· Boiling point or initial boiling point and

boiling range Not determined
Flammability Not applicable

· Lower and upper explosion limit

Lower: Not applicable
Upper: Not applicable
Flash point: Not applicable
Ignition temperature: Not determined

· Decomposition temperature:

1305-62-0 calcium dihydroxide >580 °C

· pH at 20 °C 11.5-13.5* mixed with water

· Viscosity:

Kinematic viscosityDynamic:Not applicableNot applicable

· Solubility

• water at 20 °C: < 2 g/l (Ca(OH)2)

Miscible

· Partition coefficient n-octanol/water (log

value)
Not applicable
Vapour pressure:
Not applicable.

· Density and/or relative density

Density: Not determinedRelative density Not determined

(Contd. on page 7)



Page 7/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

	(Contd. of page
Bulk density at 20 °C:	1.3-1.4* kg/m³
· Vapour density	Not applicable.
9.2 Other information	* The values are for freshly produced materia
	and may change with the time.
· Appearance:	
Form:	Powder
· Important information on protection of hea	ılth
and environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	·
· Softening point/range	
· Oxidising properties:	Not applicable
· Evaporation rate	Not applicable
· Flammable gases	Void
classes · Explosives	Void
· Aerosols	Void
· Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Sell-lieating substances and illixtures	VOIU
· Substances and mixtures which emit	
Substances and mixtures, which emit	Void
flammable gases in contact with water	Void Void
flammable gases in contact with water Oxidising liquids	Void
flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void
flammable gases in contact with water Oxidising liquids	Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Reacts with water alkaline and hardens.
- · 10.2 Chemical stability Stable under normal conditions of storage and use.
- Thermal decomposition / conditions to be avoided:

Stable at environment temperature.

No decomposition if used and stored according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Humidity

(Contd. on page 8)



Page 8/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 7)

- · 10.5 Incompatible materials: Acids
- · 10.6 Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification:		
	1305-62	2-0 cal	cium dihydroxide
Ī	Oral	LD50	>2,000 mg/kg (rat) (OECD 425)
	Dermal	LD50	>2,500 mg/kg (rabbit) (OECD 402)

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · during inhalation: Irritating to respiratory system.
- during swallowing: Irritant effect possible
- Respiratory or skin sensitisation

Product is reduced in chromate. Within the indicated storage time sensitization is not expected.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Other information (about experimental toxicology):

Experimental analysis are not available.

The product was not tested. The statements on toxicology have been derived from the properties of the individual components.

- · Subacute to chronic toxicity:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Not applicable
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
1305-62-0 calcium dihy	droxide	
NOEC	48 mg/l (Freshwater algae) (72h)	

(Contd. on page 9)



Page 9/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

		(Contd. of page 8)
	32 mg/l (marine invertebrate organisms) (14d)	
EC10/LC10 oder NOEC	2,000 mg/kg (Soil macroorganisms)	
	12,000 mg/kg (soil microorganisms)	
NOEC	1,080 mg/kg (plants) (21d)	
EC 50/48h	49.1 mg/l (freshwater invertebrate organisms)	
EC 50/72 h	184.57 mg/l (Freshwater algae)	
LC 50/96 h	457 mg/l (marine fish)	
	50.6 mg/l (freshwater fish)	
	158 mg/l (marine invertebrate organisms)	

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable
- · vPvB: Not applicable
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · AOX-indication:

Due to the substance of content which do not include organic jointed halogens, the product can not take influence on the AOX-load of the waste water.

General notes:

Do not allow product to reach ground water, water course or sewage system.

The statements on ecotoxicology have been derived from the properties of the individual components.

At present there are no ecotoxicological assessments.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Unused remainders of the product should be regarded as hazardous waste.

Recommendation for non-reusable residues: Mix with water and allow to harden.

Allow wet product and product sludge to harden and do not allow to get into drains or waterways.

Dispose hardened product as concrete waste.

European waste catalogue

17 01 01 | concrete

· Uncleaned packaging:

· Recommendation:

Non contaminated packagings may be recycled.

(Contd. on page 10)



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 9)

Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary with cleansing agents.

44.4.11N	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable
· 14.7 Maritime transport in bulk accordi	ng to
IMO instruments	Not applicable
· Transport/Additional information:	No dangerous good in sense of these transport
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

For information on labelling please refer to section 2 of this document.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- Other regulations, limitations and prohibitive regulations
- · Please note:

TRGS 200 (Germany)

TRGS 500 (Germany)

TRGS 510 (Germany)

TRGS 900 (Germany)

(Contd. on page 11)



Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.10.2022 Version number 1.0 Revision: 28.10.2022

Trade name: KEIM UNIPUTZ 1.3

(Contd. of page 10)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Department issuing SDS: KEIMFARBEN Germany, Product safety department

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

EC10: Effective concentration at 10% mortality rate.

EC50: Half maximal effective concentration.

LC10: Lethal concentration at 10% mortality rate.

NOEC: No observed effect concentration.

UK REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

- GE