



KEIM Seccopor-Fino

DECLARATION OF PERFORMANCE

Number of the declaration of performance and unique identification code of the product type
01 0026

Intended use
**Plaster for use as outside and interior plaster
for walls, ceilings, pillars and partition walls**

Manufacturer
KEIMFARBEN GMBH, Keimstraße 16, D-86420 Diedorf

System for evaluation and verification of constancy of performance
System 4

Harmonized norm
EN 998-1:2010

Declared performance

Essential characteristics	Performance
Fire behavior	A1
Water absorption	W0
Water vapor permeability	$\mu \leq 11$
Tensile adhesive strength	$\geq 0.08 \text{ N/mm}^2$ (at fracture pattern A, B or C)
Thermal conductivity (Tabular values)	$\lambda_{10, \text{dry, mat}} \leq 0,39 \text{ W/(mK)}$ for P= 50 % $\lambda_{10, \text{dry, mat}} \leq 0,43 \text{ W/(mK)}$ for P= 90 %
Durability	NPD
Hazardous substances	NPD

Performance of above stated products conforms with declared performance. Solely the manufacturer stated above is responsible for creation of the declaration of performance consistent with Regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer by:

Peter Jaser, Manager of quality assurance and color metrics

Diedorf, 26.01.2015

p.p. Peter Jaser

Appendix Material safety data sheet

Keimstraße 16 / 86420 Diedorf
Tel. +49 (0)821 4802-0
Fax +49(0)821 4802-210

Frederik-Ipsen-Straße 6 / 15926 Luckau
Tel. +49(0) 35456 676-0
Fax +49(0) 35456 676-38

www.keimfarben.de
info@keimfarben.de

Deutsche Bank München
IBAN DE37 7007 0010 0188 1580 00
BIC DEUTDE33

Stadtparkasse Augsburg
IBAN DE48 7205 0000 0000 3621 03
BIC AUGSDE77XXX

Registergericht Augsburg HRB 27263
Geschäftsführer: Rüdiger Lugert