



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022



Version number 1.0

Revision: 22.11.2022

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- **Trade name: KEIM SILAN-PRIMER**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture** Water-repellent, silane-based primer.
- **Uses advised against** All other uses are not recommended.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
KEIMFARBEN GMBH
Keimstraße 16 / 86420 Diedorf
Tel. +49 (0)821 4802-0
Fax +49 (0)821 4802-210
www.keim.com / info@keimfarben.de
- **Further information obtainable from:**
Product safety department
Telefon: 49(0)821/4802-138
E-Mail: sdb.info@keimfarben.de
- **1.4 Emergency telephone number:**
GBK GmbH Global Regulatory Compliance
Emergency number: +49(0)6132/84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Eye Irrit. 2 H319 Causes serious eye irritation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

GHS02 GHS07
- **Signal word** Danger
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/protective clothing/eye protection.
P233 Keep container tightly closed.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 1)

- P243 Take action to prevent static discharges.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with regional/national regulations.

Additional information:

Restricted to professional users.

2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable
- **vPvB:** Not applicable

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Alkylalkoxysilane / silanes + ethanol**Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	>75%
CAS: 35435-21-3 EINECS: 252-558-1 Reg.nr.: 01-2119555666-27-XXXX	Triethoxy(2,4,4-trimethylpentyl)silane ⚠ Flam. Liq. 3, H226	10-25%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	<0.3%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

When seeing the doctor we suggest to present this safety data sheet.
Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 2)

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Wash off immediately with water and soap and rinse well afterwards.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Rinse mouth and throat well with water.
Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** None known
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
carbon oxide (CO_x)
silicon dioxid (SiO₂)
- **5.3 Advice for firefighters**
- **Special protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Cool endangered receptacles with water spray.
In case of fire do not breathe smoke, fumes and vapours.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources.
Avoid contact with skin and eyes.
Do not inhale fumes.
Particular danger of slipping on leaked/spilled product.
Wear protective equipment. Keep unprotected people away.
- **6.2 Environmental precautions:**
Do not allow product to reach soil, sewage system or any water course.
Follow local governmental rules and regulations.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with non-combustible liquid-binding material (sand, earth, diatomite, vermiculite).
Ensure adequate ventilation.
Dispose of the material collected according to regulations.

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 3)

Clear contaminated areas thoroughly.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Keep receptacles tightly sealed.

Avoid contact with skin and eyes.

Do not inhale aerosols.

See item 8 (8.2) for information about suitable protective equipment and technical precautions.

Respect the protection rules.

· **Information about fire - and explosion protection:**

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

Keep in the original containers in a cool and dry place.

· **Information about storage in one common storage facility:**

Store away from oxidising agents.

Store away from water.

· **Further information about storage conditions:**

Protect from humidity and water.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Protect from heat and direct sunlight.

· **Storage class: 3**

· **GISCode** BSL50 Beschichtungsstoffe, stark lösemittelbasiert, aromatenhaltig, gekennzeichnet

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

64-17-5 ethanol

AGW (Germany)	Long-term value: 380 mg/m ³ , 200 ppm 4(II);DFG, Y
---------------	--

(Contd. on page 5)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 4)

64742-49-0 Naphtha (petroleum), hydrotreated light

MAK (Germany) | vgl.Abschn.Xb

110-54-3 n-hexane

AGW (Germany) | Long-term value: 180 mg/m³, 50 ppm
8(II);DFG, EU, Y

· DNELs

64-17-5 ethanol

Oral	Long-term - systemic effects	87 mg/kg bw/day (consumer)
Dermal	Long-term - systemic effects	206 mg/kg bw/day (consumer) 343 mg/kg bw/day (worker)
Inhalative	Acute - local effects	1,900 mg/m ³ (worker)
	Acute - local effects	950 mg/m ³ (consumer)
	Long-term - systemic effects	950 mg/m ³ (worker)
	Long-term - systemic effects	114 mg/m ³ (consumer)

35435-21-3 Triethoxy(2,4,4-trimethylpentyl)silane

Oral	Long-term - systemic effects	9.5 mg/kg bw/day (consumer)
	Acute - systemic effects	19 mg/kg/day (consumer)
Dermal	Long-term - systemic effects	13.4 mg/kg bw/day (worker)
	Long-term - systemic effects	9.5 mg/kg bw/day (consumer)
Inhalative	Acute - systemic effects	19 mg/kg/day (worker)
	Acute - systemic effects	67.8 mg/m ³ (consumer)
	Long-term - systemic effects	45 mg/m ³ (worker)
	Long-term - systemic effects	11.3 mg/m ³ (consumer)

· PNECs

64-17-5 ethanol

Aquatic compartment - freshwater	0.96 mg/l (Freshwater)
Aquatic compartment - marine water	0.79 mg/l (Seawater)
Aquatic compartment - water, intermittent releases	2.75 mg/l (not specified)
Aquatic compartment - sediment in freshwater	3.6 mg/kg sed dw (Freshwater sediment)
Terrestrial compartment - soil	0.63 mg/kg dw (soil)
Sewage treatment plant	580 mg/l (Sewage treatment plant)
Oral secondary poisoning	720 mg/kg food (food sec poisoning)

35435-21-3 Triethoxy(2,4,4-trimethylpentyl)silane

Aquatic compartment - freshwater	0.64 mg/l (Freshwater)
Aquatic compartment - marine water	0.064 mg/l (Seawater)
Aquatic compartment - water, intermittent releases	6.4 mg/l (not specified)
Aquatic compartment - sediment in freshwater	4.3 mg/kg sed dw (Freshwater sediment)
Aquatic compartment - sediment in marine water	0.43 mg/kg sed dw (Marine sediment)
Terrestrial compartment - soil	0.48 mg/kg dw (soil)

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 5)

Sewage treatment plant	1 mg/l (Sewage treatment plant)
Oral secondary poisoning	10 mg/kg food (not specified)

Ingredients with biological limit values:**110-54-3 n-hexane**

BGW (Germany)	5 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 2.5-Hexandion plus 4.5-Dihydroxy-2-hexanon (nach Hydrolyse)
---------------	---

· **Additional information:** The lists valid during the making were used as basis.

8.2 Exposure controls

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Avoid contact with the eyes and skin.

Do not inhale aerosols.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

· **Respiratory protection:** In case of long or strong exposure: gas mask filter ABEK.

· **Hand protection:** Protective gloves

· **Material of gloves**

suitable material e.g.:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.3 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

penetration time ≥ 480 min.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection:** Tightly sealed goggles

· **Body protection:** Protective work clothing

· **Environmental exposure controls**

See Section 12 and 6.2

No further relevant information available.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Fluid

(Contd. on page 7)

DEN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 6)

· Colour:	Colourless
· Odour:	Characteristic
· Odour threshold:	Not determined
· Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling range	78 °C (bei 980 hPa)
· Flammability	Not applicable
· Lower and upper explosion limit	
· Lower:	0.4 Vol %
· Upper:	15 Vol %
· Flash point:	4 °C (DIN 51755)
· Ignition temperature:	360 °C
· Decomposition temperature:	Not determined
· pH	Not determined
· Viscosity:	
· Kinematic viscosity	Not determined
· Dynamic at 20 °C:	1.27* mPas
· Solubility	
· water:	Hydrolised.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	55.9 hPa
· Density and/or relative density	
· Density at 25 °C:	0.8-0.9* g/cm ³ (bei 980 hPa)
· Relative density	Not determined
· Vapour density	Not applicable.
· 9.2 Other information	* The values are for freshly produced material and may change with the time.
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, the formation of explosive air/vapour mixtures is possible.
· Solvent content:	
· VOC (EC)	82.50 %
· Change in condition	
· Softening point/range	
· Oxidising properties:	Not applicable
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void

(Contd. on page 8)

DEN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 7)

· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids Highly flammable liquid and vapour.	
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability** Stable under normal conditions of storage and use.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** oxidizing agents
- **10.6 Hazardous decomposition products:**
In case of fire, the following can be released:
Carbon oxides (CO_x)
silicon dioxid (SiO₂)
No hazardous decomposition products if stored and handled as prescribed.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

	ATE mix	>2,000 mg/kg (orally)
64-17-5 ethanol		
Oral	LD50	10,470 mg/kg (rat) (ECHA)
Inhalative	LC50/4 h	124.7 mg/l (rat) (ECHA)

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 8)

35435-21-3 Triethoxy(2,4,4-trimethylpentyl)silane

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
	NOAEL	≥1,000 mg/kg (rat) (Analogie)

- **Skin corrosion/irritation** Frequent persistent contact with the skin may cause skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **during inhalation:** Irritant effect possible.
- **during swallowing:** Irritant effect possible
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**
Experimental analysis are not available.
The product was not tested. The statements on toxicology have been derived from the properties of the individual components.
- **Subacute to chronic toxicity:**
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)** Not applicable
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****64-17-5 ethanol**

NOEC	9.6 mg/l /(10D) (daphnia) (ECHA)
EC 50/48h	5,012 mg/l (daphnia) (ECHA)
ErC50/72h	275 mg/l (algae) (OECD 201)
LC 50/96 h	14,200 mg/l (fish) (ECHA)
EC 10	11.5 mg/l /72h (algae) (OECD 201)

35435-21-3 Triethoxy(2,4,4-trimethylpentyl)silane

NOEC	32 mg/l (daphnia) (21d)
EC 50/3h	>100 mg/l (sewage sludge)
LC 50/96 h	>100 mg/l (fish) (OECD 203)

- **12.2 Persistence and degradability** The solvent is biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 10)

DEN



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 9)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable
- **vPvB:** Not applicable
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **BOD5-value:** 60% /10 day (ECHA)
- **AOX-indication:**
According to our standard of knowledge the product does not contain any organic bounded halogen.
The product has no influence on the waste water's AOX-value.
- **According to the formulation contains the following heavy metals and compounds from the EU guideline NO. 2006/11/EC:**
According to our current data base the product does not consist of any heavy metals or substances of EU-directives 76/464/EWG.
- **General notes:**
The statements on ecotoxicology have been derived from the properties of the individual components.
Do not allow product to reach ground water, water course or sewage system.
At present there are no ecotoxicological assessments.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

- **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary with cleansing agents.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1993

(Contd. on page 11)



Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 10)

<ul style="list-style-type: none">· 14.2 UN proper shipping name· ADR· IMDG, IATA	1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ALKYLTRIETHOXYSILANE), special provision 640C FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), ALKYLTRIETHOXYSILANE)
<ul style="list-style-type: none">· 14.3 Transport hazard class(es)· ADR, IMDG, IATA 	<ul style="list-style-type: none">· Class 3 Flammable liquids.· Label 3
<ul style="list-style-type: none">· 14.4 Packing group· ADR, IMDG, IATA	II
<ul style="list-style-type: none">· 14.5 Environmental hazards:· Marine pollutant:	No
<ul style="list-style-type: none">· 14.6 Special precautions for user· Hazard identification number (Kemler code):· EMS Number:· Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
<ul style="list-style-type: none">· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
<ul style="list-style-type: none">· Transport/Additional information:	
<ul style="list-style-type: none">· ADR· Limited quantities (LQ)· Excepted quantities (EQ)· Transport category· Tunnel restriction code	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E
<ul style="list-style-type: none">· IMDG· Limited quantities (LQ)· Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 12)

DEN



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 11)

- | | |
|---------------------------------|---|
| · UN "Model Regulation": | UN 1993 FLAMMABLE LIQUID, N.O.S.
(ETHANOL (ETHYL ALCOHOL),
ALKYLTRIETHOXYSILANE), 3, II |
|---------------------------------|---|

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
For information on labelling please refer to section 2 of this document.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Seveso category P5c** FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (ANNEX XIV)**

None of the ingredients is listed.

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**

- **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

- **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

- **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

- **National regulations:**

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

- **Other regulations, limitations and prohibitive regulations**

- **Please note:**

TRGS 200 (Germany)

TRGS 500 (Germany)

TRGS 510 (Germany)

TRGS 900 (Germany)

- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable

(Contd. on page 13)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 1.0

Revision: 22.11.2022

Trade name: KEIM SILAN-PRIMER

(Contd. of page 12)

- **Product-Code/Giscode:** BSL50
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** KEIMFARBEN Germany, Product safety department

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- AGW: Arbeitsplatzgrenzwert (Germany)
- EC10: Effective concentration at 10% mortality rate.
- EC50: Half maximal effective concentration.
- LC10: Lethal concentration at 10% mortality rate.
- NOEC: No observed effect concentration.
- REACH: Registration, Evaluation and Authorisation of Chemicals (Regulation (EC) No.1907/2006)
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2