



TECHNICAL DATA SHEET

HILTI DÜBELTELLER HDT 140

1. PRODUCT DESCRIPTION

Plastic anchor plate for Hilti HTR-P screw anchors. European Technical Assessment (ETA): ETA-16/0116.

2. FIELD OF APPLICATION

In conjunction with Hilti HTR-P screw anchors, for mounting mineral wool slats flush with the surface. Applicable in KEIM system approvals AquaROYAL-System; Klassik Plus-System; Klassik-System

3. PRODUCT PROPERTIES

- easy and fast processing
- reduces the dowel quantities

MATERIAL CHARACTERISTICS:

- Colour shade: white

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Check the adhesion of the insulation panels after at least 3 days. Insulation panels that are not bonded or damaged must be replaced.

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying from min. 0 °C to max. 40 °C. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

APPLICATION:

Before setting the anchor, the HILTI Dübelteller HDT 140 must be pushed over the anchor shaft onto the anchor plate and, if necessary, locked into place.

5. LIEFERFORM

LIEFERFORM

Product name	Plate diameter	Pieces per unit	Type of container
HILTI Dübelteller HDT 140 weiß	140 mm	100	carton
HILTI Dübelteller HDT 90 weiß	90 mm	100	carton

TECHNICAL DATA SHEET – HILTI DÜBELTELLER HDT 140

6. LAGERUNG

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering

7. ENTSORGUNG

ENTSORGUNG

Waste code: 17 09 04

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de