



## TECHNICAL DATA SHEET

# KEIM KALK-SINTERWASSER

## 1. PRODUCT DESCRIPTION

---

KEIM Kalk-Sinterwasser is a saturated and ready-to-use solution of pit lime filler in water.

## 2. FIELD OF APPLICATION

---

KEIM Kalk-Sinterwasser can be used as a thinner for KEIM Athenit-lucente or KEIM Athenit-forte lime paints. For a more stable coating, pre-wet highly absorbent substrates with KEIM Lime Sinter Water. Old and weakly chalking lime coatings in the interior can be consolidated with KEIM Kalk-Sinterwasser.

## 3. PRODUCT PROPERTIES

---

- non-yellowing
- environmentally friendly
- extremely vapour permeable
- absolutely lightfast
- anti-fungal and anti-algae thanks to natural alkalinity
- fire behaviour: non-flammable
- no synthetic binders
- no solvents added
- no plant-based resins

### MATERIAL CHARACTERISTICS:

- Density: approx. 1.0 - 1.1 g/cm<sup>3</sup>

### COMPOSITION:

water, calcium hydroxide, natural carbohydrates.

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

The substrate must be strong, dry, clean, sound and free from adhesion-reducing residues.

### APPLICATION CONDITIONS:

Ambient and substrate temperature  $\geq 5$  °C during application and drying. Do not apply in direct sunlight or on sun-heated substrates. Protect surfaces from direct sun, wind and rain during and after application.

### APPLICATION:

KEIM Kalk-Sinterwasser can be applied with a brush, the KEIM facade coating device or the Chiron device. KEIM Kalk-Sinterwasser is formulated ready for use and must not be diluted with water. For unstable chalking old coatings, saturate the substrate.

### DRYING TIME:

Can be overcoated after 4 hours at the earliest (at 23 °C and 50% RH). At higher relative humidity, layer thicknesses and/or lower temperatures, drying is delayed accordingly. (In colder seasons up to one day).

## TECHNICAL DATA SHEET – KEIM KALK-SINTERWASSER

---

### CONSUMPTION:

approx. 0,2 l/m<sup>2</sup>, Application as primer.

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

### CLEANING OF TOOLS:

Clean immediately with water.

## 5. PACKAGING

---

| Container content | Unit of measure | Quantity on pallet | Type of container |
|-------------------|-----------------|--------------------|-------------------|
| 20                | l               | 24                 | jerry can         |
| 5                 | l               | 96                 | jerry can         |

## 6. STORAGE

---

| max. storage time | Storage conditions                                   |
|-------------------|--|
| 12 months         | cool<br>frost-free<br>keep container tightly sealed. |

## 7. DISPOSAL

---

For disposal information refer to section 13 of the safety data sheet.

### EC WASTE CODE:

Waste code: 06 02 99

## 8. SAFETY INSTRUCTIONS

---

Please, refer to the Material Safety Data Sheet.

### GISCODE:

GIS code: BSW 60

## 9. GENERAL INFORMATION

---

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

## 10. CERTIFICATES & QUALITY SEALS

---

## TECHNICAL DATA SHEET – KEIM KALK-SINTERWASSER

---



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



**KEIMFARBEN GMBH**

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210  
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38  
[www.keim.com](http://www.keim.com) / [info@keimfarben.de](mailto:info@keimfarben.de)