



TECHNICAL DATA SHEET

KEIM PVC-SOCKELGRUNDPROFIL

1. PRODUCT DESCRIPTION

Base profile made of rigid PVC can be used in conjunction with PVC base insertion profile.

2. FIELD OF APPLICATION

For the creation of a thermal-bridge-free, variable, as well as sufficiently tight and dimensionally stable system termination in the base area by mounting on the substrate in combination with base base and base insertion profile, for insulation thicknesses from 60 mm to 240 mm.

3. PRODUCT PROPERTIES

- especially economical
- easy and fast processing
- suitable for all insulation panel thicknesses and kinds
- thermal bridge free
- resistant to aging

MATERIAL CHARACTERISTICS:

- Width: 60 - 90, 100 - 160, 180 - 240 mm
- length: 2,00 m
- Colour shade: white

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

The substrate must be strong, dry, clean, sound and free from adhesion-reducing residues. Unevenness of up to 1 cm/m may be bridged. Larger unevenness must be mechanically levelled or by applying a render in accordance with DIN EN 998-1.

CONSUMPTION:

approx. 1,0 m/m

APPLICATION:

Reach of the profiles is to be selected according to insulation panel thickness. According to the defined height, the profiles should be aligned in a horizontal and flush position and fixed with impact dowels ejot ND-K (3 pieces/m). The two outer drill holes are to be used for fixing. To level out possible substrate unevenness use KEIM distance pieces. A suitable joint sealing tape must be applied to the lower edge of the rear side of the profile towards the substrate.

TECHNICAL DATA SHEET – KEIM PVC-SOCKELGRUNDPROFIL

5. LIEFERFORM

Product name	Panel thickness [mm]	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
PVC- Sockelgrundprofil 60 - 90 mm	60 - 90	2.00	10	20.00	carton
PVC- Sockelgrundprofil 100 - 160 mm	100 - 160	2.00	10	20.00	carton
PVC- Sockelgrundprofil 180 - 240 mm	180 - 240	2.00	10	20.00	carton

LIEFERFORM

Product name	Panel thickness [mm]	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
PVC- Sockeleinsteckprofil 60 - 90 mm	60 - 90	2.00	10	20.00	carton
PVC- Sockeleinsteckprofil 100 - 240 mm	100 - 240	2.00	10	20.00	carton
Distanzstücke	3, 5, 8, 10, 15		100		carton

LIEFERFORM

Delivery in cartons

6. LAGERUNG

max. storage time	Lagerungsbedingungen
no maximum storage time	even avoid deflection

7. ENTSORGUNG

ENTSORGUNG

Waste code: 17 09 04

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

TECHNICAL DATA SHEET – KEIM PVC-SOCKELGRUNDPROFIL

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de