



## TECHNICAL DATA SHEET

# KEIM PUTZGRUND

## 1. PRODUCT DESCRIPTION

---

KEIM Putzgrund is a silicate primer with a rough surface and good filling and covering properties.

## 2. FIELD OF APPLICATION

---

KEIM Putzgrund is suitable for interior and exterior use.

KEIM Putzgrund is used as a primer for KEIM brilliant render on old and new plasters of mortar groups PII and PIII as well as on gypsum plasters and gypsum plasterboards indoors. KEIM Putzgrund reduces the absorbency of the substrate and increases the open time of KEIM Brilliantputz. The rough, non-slip surface allows for optimal application of KEIM Brilliantputz even on very smooth substrates.

## 3. PRODUCT PROPERTIES

---

### MATERIAL CHARACTERISTICS:

- Density: approx. 1.4 - 1.6 g/cm<sup>3</sup>

### CLASSIFICATION:

- Diffusion-equivalent air layer thickness (sd-value): < 0,02 m

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

Allow new base plasters to cure for at least 14 days!

### APPLICATION:

KEIM Putzgrund If necessary, only dilute with max. 10 % with Spezial-Fixativ. Apply evenly with a brush or roller.

### DRYING TIME:

Can be overcoated after 12 hours at the earliest (at 23 °C and 50% RH). At higher relative humidity, layer thicknesses and/or lower temperatures, drying is delayed accordingly.

### CONSUMPTION:

approx. 0,3 kg/m<sup>2</sup>

These material consumption values are guide values for smooth substrates. Exact consumption values must be determined by means of test areas.

### CLEANING OF TOOLS:

Clean immediately with water.

## TECHNICAL DATA SHEET – KEIM PUTZGRUND

---

### 5. PACKAGING

---

Container content	Unit of measure	Quantity on pallet	Type of container
25	kg	24	bucket

### 6. STORAGE

---

max. storage time	Storage conditions
12 months	cool frost-free

### 7. DISPOSAL

---

For disposal information refer to section 13 of the safety data sheet.

#### EC WASTE CODE:

Waste code: 08 01 12

### 8. SAFETY INSTRUCTIONS

---

Please, refer to the Material Safety Data Sheet.

#### GISCODE:

GIS code: BSW 10

### 9. GENERAL INFORMATION

---

Cover surfaces not to be treated, especially glass, ceramics and natural stone. Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water.

Mixing with products not part of the system or other foreign additives is not permitted.

### 10. CERTIFICATES & QUALITY SEALS

---



The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210  
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38  
www.keim.com / info@keimfarben.de