



## TECHNICAL DATA SHEET

# KEIM STR-RONDELLE

## 1. PRODUCT DESCRIPTION

---

Specially matched system rondels made of mineral wool or polystyrene (EPS).

## 2. FIELD OF APPLICATION

---

For recessed installation according to the EJOT STR principle.  
For use with ejothem STR U 2G, ejothem STR H A2 and STR H.

## 3. PRODUCT PROPERTIES

---

- ready to use
- easy and fast processing

### MATERIAL CHARACTERISTICS:

- Colour shade: assorted colours

## 4. APPLICATION INSTRUCTIONS

---

### APPLICATION:

After recessed installation, the anchor plate must be covered with Ejothem STR-Rondelle MW/EPS-grey, after surface-flush installation, the anchor shaft must be closed with the Ejoth STR plug.

### AFTERTREATMENT:

After recessed installation, the anchor plate must be covered with Ejothem STR-Rondelle MW/EPS-grey, after surface-flush installation, the anchor shaft must be closed with the Ejoth STR plug.

## 5. DELIVERY FORM

---

Product name	Pieces per unit	Type of container
STR-Rondelle-MW	100	carton
STR-Rondelle-EPS grau	100	carton

## 6. STORAGE

---

max. storage time	Storage conditions
no maximum storage time	dry

## TECHNICAL DATA SHEET – KEIM STR-RONDELLE

---

### 7. DISPOSAL

---

No special notes.

### 8. SAFETY INSTRUCTIONS

---

No particular indications.

### 9. GENERAL INFORMATION

---

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



**KEIMFARBEN GMBH**

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210  
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38  
[www.keim.com](http://www.keim.com) / [info@keimfarben.de](mailto:info@keimfarben.de)