



TECHNICAL DATA SHEET

KEIM TROPFKANTENPROFIL W40-2

1. PRODUCT DESCRIPTION

Plastic drip edge profile, with fabric.

2. FIELD OF APPLICATION

For forming drip edges on insulated soffits. For thin-layer and thick-layer construction.

3. PRODUCT PROPERTIES

- suitable for all insulation panel thicknesses and kinds
- easy and fast processing
- easy to use
- driving rain-proof
- fire behaviour: hardly inflammable B1 according to 4102
- non-slip
- very good adhesion
- highly weather-resistant
- long-lasting

MATERIAL CHARACTERISTICS:

- Colour shade: white

4. APPLICATION INSTRUCTIONS

APPLICATION CONDITIONS:

Ambient and substrate temperature during application and drying must be in the range between max. 5 °C and max. 30 °C.

APPLICATION:

Cut to size with anvil shears or suitable angle sander.

KEIM Tropfkantenprofil W40-2 is to be applied before the application of the base coat.

REINFORCEMENT:

Apply the system's reinforcing mortar at the appropriate points and embed KEIM Tropfkantenprofil W40-2 centrally or in the upper third, free of bubbles and folds.

The layer thickness for embedding in thin-layer systems should not be less than 2 mm and not exceed 3 mm to achieve the best possible functionality. In thick-layer systems, use close to the surface is recommended wherever possible.

AFTERTREATMENT:

After complete drying of the base coat, the surface is reinforced.

TECHNICAL DATA SHEET – KEIM TROPFKANTENPROFIL W40-2

5. LIEFERFORM

Product name	Mesh size	Length [m]	Pieces per unit	Inhalt je VE [m]	Type of container
Tropfkantenprofil W 40-2	4 x 4 mm	2.00	10	20.00	carton

LIEFERFORM

Delivery in cartons

6. LAGERUNG

max. storage time	Storage conditions
no maximum storage time	dry protect against weathering flat-lying in the outer cardboard

7. ENTSORGUNG

ENTSORGUNG

Waste code: 17 09 04

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de