



TECHNICAL DATA SHEET

EJOTHERM S1 TOOL

1. PRODUCT DESCRIPTION

Self-decoupling assembly tool.

2. FIELD OF APPLICATION

For mounting ejotherm S1 flush with the surface, with patented bit finding (S1 Tool Pro).

3. PRODUCT PROPERTIES

- Efficient setting times
- easy to use
- Robust design for long service life
- Adjustable hexagonal shank for use with standard drill chuck
- long-lasting

MATERIAL CHARACTERISTICS:

- Colour shade: grey

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Check the adhesion of the insulation panels after at least 3 days. Insulation panels that are not bonded or damaged must be replaced. Drill the hole at right angles to the surface of the anchoring base.

The drill hole must be at least 10 mm deeper than the minimum anchorage depth.

Remove drill dust from the drill hole.

APPLICATION:

Use only in conjunction with the ejotherm S1 screw anchor. Place the bit on the screw head and screw in the screw at an appropriate speed. The ejotherm S1 Tool disengages automatically when the anchor plate is correctly seated.

5. DELIVERY FORM

Product name	Pieces per unit	Type of container
ejotherm S1 Tool	1	piece
ejotherm S1 Tool Pro*	1	piece

DELIVERY FORM ADDITIONAL INFORMATION

*with patented bit finding

TECHNICAL DATA SHEET – EJOTHERM S1 TOOL

6. STORAGE

max. storage time	Storage conditions
no maximum storage time	dry

7. DISPOSAL

No special notes.
Waste metal

8. SAFETY INSTRUCTIONS

No particular indications.

9. GENERAL INFORMATION

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38
www.keim.com / info@keimfarben.de