



TECHNICAL DATA SHEET

EJOTHERM STR-TOOL 2GE

1. PRODUCT DESCRIPTION

Specially adapted assembly tool with adjustable metal shaft, hexagon compatible with standard drill chuck. Set consisting of: ejotherm STR-tool 2GE, additional cutting plates, offset screwdriver as well as screw bits.

2. FIELD OF APPLICATION

For recessed installation of ejotherm STR U 2G, can alternatively also be used for ejotherm STR H and STR H A2. Adjustable shaft can also be used for flush mounting.

3. PRODUCT PROPERTIES

4. APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION:

Check the adhesion of the insulation panels after at least 3 days. Insulation panels that are not bonded or damaged must be replaced.

APPLICATION INSTRUCTIONS

Anchoring is carried out in glued and dowelled ETIC systems using ETICS fasteners approved by the general building authorities or by the European authorities according to DIN EN 1991-1-4/NA. The required dowel quantity depends on the building height and the respective wind zone in which the object is located. Countersunk installation is only possible from 100 mm insulation panel thickness. For further information, please refer to our ETICS Technical Guide, Chapter #8, ETICS Wind Suction Loads.

5. LIEFERFORM

Product name	Inhalt je VE	Type of container
STR-Tool 2GE	1	set

6. LAGERUNG

max. storage time	Storage conditions
no maximum storage time	flat-lying in the outer cardboard

7. ENTSORGUNG

8. SICHERHEITSHINWEISE

no particular indications

9. ALLGEMEINE HINWEISE

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.