



## TECHNICAL DATA SHEET

# KEIM CONCRETAL® FINE FILLER DILUTION (SPEZIALVERGÜTUNG)

## 1. PRODUCT DESCRIPTION

Water-dilutable dilution for KEIM Fine Finishing Mortar.

## 2. FIELD OF APPLICATION

Addition to mixing water for KEIM Fine Finishing Mortar to produce blowhole grout.

## 3. APPLICATION INSTRUCTIONS

### Substrate preparation

The substrate must be sound, clean and free of loose material, dust, oil, grease and other substances having a release action. The substrate should be roughened by blasting.

Slight pre-wetting may be required, but the substrate must not be saturated with water.

### Application

Mixing ratio at approx. 20°C:

Blowhole grout:  
25 kg KEIM Fine Finishing Mortar  
4.5 l Water  
1.5 l KEIM Concretal-Fine Filler Dilution

KEIM Concretal- Fine Filler Dilution is first added to the mixing water and thoroughly mixed, after which the KEIM Fine Finishing Mortar is mixed.

Materials can then be applied by trowel, squeegee or float onto a pre-wetted surface and struck off to the required finish

Trials are recommended for specific substrate and temperature conditions.

### Application conditions

Ambient and substrate temperature above 5°C and below 30°C. Do not apply in direct sunlight or onto sun-heated surfaces, nor if it is raining or if there is an immediate likelihood of rain.

### Consumption

Approx. 60 ml per m<sup>2</sup> and per mm of blowhole grout.

Consumption rates are offered for guideline purposes only and are quoted for smooth surfaces. Actual rates are the responsibility of the applicator. Project specifications should be referred to for specific rates.

### Over-coating

After at least 5 days have elapsed at 20°C.

### Cleaning of tools

Clean immediately after use with water.

## 4. PACKAGING

5 lt containers

## 5. STORAGE

Shelf life is approx. 12 months if kept dry, cool, but frost-free in tightly closed containers. Protect from moisture.

## 6. DISPOSAL

EC Waste Code No. 08 01 12.

Any residues must be emptied out of containers before recycling

## **7. SAFETY INSTRUCTIONS**

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Please, refer to the EC Material Safety Data Sheet

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.



KEIM MINERAL PAINTS LTD  
Santok Building, Deer Park Way  
Donnington Wood, Telford  
Shropshire TF2 7NA

Tel. 01952 231250  
Fax. 01952 231251  
[www.KEIMpaints.co.uk](http://www.KEIMpaints.co.uk)  
[sales@KEIMpaints.co.uk](mailto:sales@KEIMpaints.co.uk)