



TECHNICAL DATA SHEET

KEIM SOLIPRIM

1. PRODUCT DESCRIPTION

KEIM Soliprim is a special silicate primer for interior use based on a binder combination of hydrosol and silica sol.

2. FIELD OF APPLICATION

KEIM Soliprim may be used

- to equalise differing levels of absorbency of mineral and organic substrates, sound existing coatings or mixed substrates.
- to fix and consolidate chalking or sanding substrates.
- to optimise surface homogeneity of subsequent coats of paint, in particular under difficult light conditions.

3. PRODUCT PROPERTIES

- Binder basis: hydrosol and silica sol
- Equalising
- Highly effective for substrate consolidation
- Promotes adhesion
- Penetrates deep into the material
- Breathable, microporous
- Slight silicifying action
- No solvents added
- Low odour

Material characteristics:

- Specific weight: approx. 1.0 - 1.1
- s_d value: < 0.01m
- pH-value: approx. 9
- Organic content: < 5%

Colour shade:

Slightly milky

4. APPLICATION INSTRUCTIONS

Substrate preparation:

The substrate must be dry, clean and free of grease.

Application:

Apply KEIM Soliprim preferably undiluted with a brush. Roller or spray application are also possible. Avoid shiners. Highly absorbent substrates may need two coats applied wet-on-wet.

Note:

KEIM Soliprim cannot be used as dilution.

Application conditions:

Air and substrate temperature > 5°C

Drying time:

A drying time of at least 6 hours must be left between primer and subsequent coat.

Consumption:

0.1–0.2 l/m² per coat depending on the absorbency of the substrate. Determine precise consumption by trial application on object.

Cleaning of tools:

Clean with water immediately after use.

5. PACKAGING

5 and 20 l containers

6. STORAGE

5 and 20 l containers

7. DISPOSAL

EC Waste Code No. 08 01 11*

Any residues must be emptied out of containers before recycling.



8. SAFETY INSTRUCTIONS

Giscode: BSW50

KEIM Soliprim is slightly alkaline.

Provide appropriate protection for surfaces which are not to be treated (e.g. glass, ceramics, wood etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Please refer to the EC Safety Data Sheet.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.



KEIMFARBEN GMBH

Keimstraße 16 / 86420 Diedorf / Tel. +49 (0)821 4802-0 / Fax +49 (0)821 4802-210
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 (0)35456 676-0 / Fax +49 (0)35456 676-38
www.keim.com / info@keimfarben.de